

# Using X-ray Computed Tomography to Describe the Dynamics of Nitrous Oxide Emissions during Soil Drying

Eva Rabot, Marine Lacoste, Catherine Hénault, Isabelle Cousin

# ▶ To cite this version:

Eva Rabot, Marine Lacoste, Catherine Hénault, Isabelle Cousin. Using X-ray Computed Tomography to Describe the Dynamics of Nitrous Oxide Emissions during Soil Drying. Vadose Zone Journal, 2015, 14 (8), 10 p. 10.2136/vzj2014.12.0177. insu-01241590

# HAL Id: insu-01241590 https://insu.hal.science/insu-01241590v1

Submitted on 10 Dec 2015

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.





# Using X-ray computed tomography to describe the dynamics of nitrous oxide emissions during soil drying

Journal:	Vadose Zone Journal
Manuscript ID:	VZJ-2014-12-0177-ORA.R1
Manuscript Type:	Original Research Articles
Date Submitted by the Author:	10-Apr-2015
Complete List of Authors:	RABOT, Eva LACOSTE, Marine Henault, Catherine Cousin, Isabelle
Keywords:	soil, nitrous oxide, X-ray computed tomography, gas diffusivity, pore connectivity

SCHOLARONE™ Manuscripts

- 1 Using X-ray computed tomography to describe the dynamics of nitrous oxide emissions
- 2 during soil drying
- 3 E. Rabot<sup>1,2</sup>, M. Lacoste<sup>2</sup>, C. Hénault<sup>2</sup>, I. Cousin<sup>2,\*</sup>
- 4 Laboratoire Léon Brillouin, UMR12, CEA Saclay, 91191 Gif-sur-Yvette Cedex, France
- 5 <sup>2</sup> INRA, UR0272, UR Science du Sol, F-45075 Orléans, France
- \* Corresponding author: isabelle.cousin@orleans.inra.fr

#### 7 Impact statement

- 8 We proposed a methodology to image the water dynamics and the soil structure of a soil
- 9 sample with X-ray computed tomography, while controlling the hydric state and monitoring
- 10 N<sub>2</sub>O fluxes. Relevant information about N<sub>2</sub>O transport could be extracted from the images.

#### 11 Abstract

- Water in soil is known to be a key factor for controlling nitrous oxide (N<sub>2</sub>O) emissions,
- because N<sub>2</sub>O is mainly produced by denitrification in anoxic environments. In this study, we
- proposed a methodology to image the water and soil structure of a soil sample with X-ray
- 15 computed tomography, while controlling the hydric state and monitoring N<sub>2</sub>O fluxes. We
- used a multistep outflow system to apply two wetting-drying cycles to an undisturbed soil.
- 17 The soil core was scanned with coarse-resolution X-ray computed tomography, one time
- during wetting and several times during drying, to measure quantitative and qualitative
- indicators of the pore network. Nitrous oxide emissions were higher during the first (C1) than
- during the second (C2) wetting-drying cycle, both for the wetting and the drying phases.
- 21 Fluxes increased quickly after the beginning of the drying phase to reach a peak after 5 h.
- 22 Differences in the intensity of N<sub>2</sub>O emissions between the two cycles were attributed to
- 23 differences in the water saturation, air-phase connectivity, and relative gas diffusion
- coefficient, which led to more or less N<sub>2</sub>O production, consumption, and entrapment in soil.
- 25 The speed of the N<sub>2</sub>O emissions at the beginning of the drying phase depended on the rate of
- 26 increase of the air-filled pore volume and connectivity, and was especially well described by
- 27 the estimated relative gas diffusion coefficient. Parameters of the soil structure were not able
- 28 to explain completely the intensity of N<sub>2</sub>O emissions during drying: N<sub>2</sub>O production and
- 29 consumption factors were also involved.

- 30 **Abbreviations:** C1: first wetting-drying cycle; C2: second wetting-drying cycle; WFPS:
- 31 water filled pore space.

#### 1 Introduction

32

33 Nitrous oxide (N<sub>2</sub>O) concentration in the atmosphere is constantly increasing (Khalil et al., 34 2002). With a global warming potential 300 times higher than that of carbon dioxide over a 35 100-year time scale (World Meteorological Organization, 2007), N<sub>2</sub>O is the gas with the third 36 largest contribution to global warming (Ciais et al., 2013). Nitrous oxide plays also an 37 important role in the stratospheric ozone depletion (Ravishankara et al., 2009). Soils are a 38 major source of N<sub>2</sub>O, accounting for 60% of natural sources (soils under natural vegetation) 39 and 60% of anthropogenic sources (soils used for agriculture; Ciais et al., 2013). Nitrous 40 oxide is produced during the natural microbial reactions of nitrification and denitrification, 41 two reactions which are controlled by the status of aerobiosis in soils. Since the water 42 saturation of soils modifies the ratio between water-filled and air-filled pore space, the water-43 filled pore space (WFPS) is often used as an indicator of N<sub>2</sub>O emissions (Butterbach-Bahl et 44 al., 2013; Robertson, 1989). In particular, wetting and drying cycles are known to affect N<sub>2</sub>O 45 emissions (Guo et al., 2014; Muhr et al., 2008). Peaks of N<sub>2</sub>O emissions have often been 46 observed both in the field and in laboratory experiments after the rewetting of a soil 47 (Groffman and Tiedje, 1988; Sanchez-Martin et al., 2010; Sexstone et al., 1985). 48 Following the model proposed by Smith (1980), N<sub>2</sub>O production can occur inside anoxic 49 aggregates and then diffuse to the soil surface through inter-aggregate pores. Thus, delays 50 between microbial production and the moment when N<sub>2</sub>O can be measured at the soil surface 51 have been demonstrated (Clough et al., 1998; McCarty et al., 1999; Rabot et al., 2014; Weier 52 et al., 1993; Wollersheim et al., 1987). Delays in N<sub>2</sub>O emissions are partly linked to gas 53 entrapment and the associated dissolution of N<sub>2</sub>O in the water phase (Clough et al., 2005). We 54 hypothesize here that introducing dynamic indicators of the soil structure could enhance our

55	understanding of the dynamic nature of N <sub>2</sub> O emissions during wetting and drying cycles, by a
56	better description of N <sub>2</sub> O transport. Indeed, since soil structure controls the water and gas
57	dynamics in soils, and thus the aerobic microbial activity, soil structure is supposed to be of
58	great importance for N <sub>2</sub> O emissions (Ball, 2013).
59	Both the soil water and soil structure can be studied by X-ray computed tomography. X-ray
60	computed tomography is rapid, non-destructive, and allows successive scans over time while
61	measuring other dynamic parameters, such as N <sub>2</sub> O fluxes. It provides 3-D images, used to
62	perform spatial analysis of the soil sample. In soil science, X-ray computed tomography is a
63	common tool, used for example to study the effect of agricultural practices (Deurer et al.,
64	2009; Schjønning et al., 2013; Schlüter et al., 2011), the water dynamics (Kasteel et al., 2000;
65	Sammartino et al., 2012; Wildenschild et al., 2005), or the gas dynamics (Deurer et al., 2009;
66	Katuwal et al., 2014; Naveed et al., 2013). Katuwal et al. (2014) demonstrated the interest of
67	coarse-resolution X-ray scanners to study gas transport functioning in macropores. This
68	methodology can be applied to N <sub>2</sub> O emissions. Only few studies used imaging techniques to
69	study greenhouse gas emissions (e.g., Mangalassery et al., 2014; Mangalassery et al., 2013),
70	and to our knowledge, none of them monitored greenhouse gases while acquiring images of
71	the soil structure.
72	In this study, we proposed a methodology to image the water and soil structure of a soil
73	sample with coarse-resolution X-ray computed tomography, while controlling the hydric state
74	and monitoring N2O fluxes. We aimed at demonstrating which relevant information can be
75	extracted from the images to allow a better understanding of N <sub>2</sub> O emissions. We illustrated
76	this methodology by subjecting a soil sample to two wetting and drying cycles.

#### 2 Material and methods

77

78

#### 2.1 Soil sampling, physical and chemical characterization

79 The study site was chosen for the high N<sub>2</sub>O emissions previously recorded in the field (Gu et 80 al., 2011), at the same location as the study of Rabot et al. (2014). The site is an agricultural 81 field cultivated with rape (Brassica napus L.), located near Chartres, in the northwest of 82 France (48.376° N lat, 1.196° E long). The soil is classified as Glossic Retisol (WRB, 2014), 83 with a clay content of 13.7%, a silt content of 82.0%, and a sand content of 4.3% (Rabot et al., 84 2014). A soil core was collected in June 2013 in a PVC cylinder (13.2-cm inner diameter by 85 7-cm height) from the surface horizon (1–8 cm). Bulk soil was also sampled in the surface 86 horizon for physical and chemical analyses. Soil organic carbon was measured by 87 sulfochromic oxidation, and total nitrogen was measured by the Dumas method. The soil 88 nitrate content was determined by colorimetric analysis after the extraction from an 8-g soil 89 sample using 0.5 M K<sub>2</sub>SO<sub>4</sub>. Soil pH was determined in a 1:2.5 soil/water volume ratio on samples sieved at < 2 mm. At the sampling time, the soil organic carbon was 9.5 g kg<sup>-1</sup>, the 90 total nitrogen content was 0.91 g kg<sup>-1</sup>, the nitrate content was 51.3 mg NO<sub>3</sub><sup>-</sup>-N kg<sup>-1</sup>, and the 91 soil pH was 5.6. The porosity of the soil sample was 0.46 cm<sup>3</sup> cm<sup>-3</sup> and the volumetric water 92 93 content was 37.7% (equivalent to 81.9% WFPS). The sample was conditioned in a plastic bag 94 and stored field moist during two weeks at 5°C to minimize microbial activity. Before the 95 start of the experiment, the soil core was trimmed on each end and maintained at 20°C for 24 96 h.

#### 2.2 Experimental setup

97

The experiment consisted in controlling the hydric status of the soil sample with a multistep outflow system (Weihermüller et al., 2009): the soil cylinder was connected to a water-tank to control its wetting according to the Mariotte bottle principle, and connected to a vacuum

pump and a sampling bottle to control its drying (Fig. 1). Hydraulic continuity was ensured
with a porous ceramic plate (1-bar air-entry value, $8.6 \times 10^{-8} \text{ m s}^{-1}$ saturated hydraulic
conductivity, Soilmoisture Equipment Corp.) placed at the bottom of the soil cylinder and
previously saturated with water. The soil cylinder-ceramic plate system was sealed with
silicon to avoid water or gas leaks. Both the water content and water potential were
continuously monitored during the experiment, with a balance (0.1 g precision) and two
microtensiometers (porous ceramic cup, 20-mm length, 2.2-mm diam., 150-kPa air-entry
value) inserted at 2 and 4 cm from the cylinder surface at the end of the wetting phase. Data
were recorded every 10 min with a datalogger (CR1000, Campbell Scientific).
Two wetting-drying cycles (hereafter referred to as the C1 and C2 cycles) were applied to the
soil cylinder. The initial water content for C1 was the water content at sampling. The sample
was first saturated for 3 d by raising the water level to the soil surface in one step, and then a
-100 hPa pressure was applied at the bottom of the soil core in one step, and maintained for
about 7 h (C1 cycle). A zero hPa pressure was then applied for 3 d, followed by a -100 hPa
pressure for about 7 h (C2 cycle). Indeed, Rabot et al. (2014) demonstrated that $N_2O$ peaks
can be created during the drying phase, at a matric potential of approximately -50 hPa. We
chose thus to apply a pressure lower than this value of -50 hPa. The speed of the matric
potential decrease was much higher that under natural conditions, and could affect the water
transport and hydraulic continuity. We used a KNO3 solution as the wetting fluid, to ensure
that nitrate was not a limiting factor for N <sub>2</sub> O emissions during the wetting phase, and to
isolate the effects of nitrate concentration and soil moisture on the $N_2O$ emissions. Hénault
and Germon (2000) showed that the response of $N_2\mathrm{O}$ emissions to the nitrate concentration
could be described by a Michaelis-Menten function. We used a nitrate concentration at the
plateau of this function (4.1 mM N). The nitrate solution was prepared with de-aired water to
prevent air hubble formation during the experiment

Nitrous oxide emissions were monitored by infrared correlation spectroscopy (N<sub>2</sub>O Analyzer model 46i, Thermo Scientific) using a 4-L volume closed-chamber. The emissions were measured for 20-min periods, and the concentration value was recorded every minute. Given the linear increase of the N<sub>2</sub>O concentration in the closed-chamber, N<sub>2</sub>O fluxes were calculated linearly from the observed change in concentration during the first 10 min after the chamber was closed. Only one N<sub>2</sub>O flux measurement was done during wetting, at the end of each wetting phase for each cycle, and seven (respectively eight) flux measurements were recorded during the drying phase for the C1 (respectively C2) cycle. Moreover, gases inside the chamber were sampled in evacuated vials at the end of the wetting phase and at the middle of the drying phase (3.5 h after the beginning of the drying phase), and CO<sub>2</sub> concentration was determined by gas chromatography (µGC Gas Analyzer T-3000, SRA Instruments). For a single CO<sub>2</sub> flux measurement, the atmosphere of the closed-chamber was sampled three times during 20-min periods. Given the linear increase of the CO<sub>2</sub> concentration, the flux was then calculated linearly. The chamber was removed before each measurement to restore the atmosphere to ambient concentrations of gases. The sample was kept inside the scanner during the two wetting-drying cycles. The temperature inside the scanner room was monitored and ranged between 22.5 and 25.5°C throughout the experiment.

#### 2.3 Computed tomography and image analyses

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

The soil sample was placed in the scanner in its sampling direction. The soil sample was scanned one time at the end of the wetting phase, and the vacuum pump was then activated to begin the soil drying. We then scanned the sample seven times for C1, and nine times for C2 during the drying phase, alternating with N<sub>2</sub>O flux measurements. Two scans have been added at C2 compared to C1 to refine the results just after the beginning of the drying phase. We used a medical X-ray tomograph (Siemens Somatom Definition AS) operating at an energy

level of 200 kV and a current of 140 mA. The voxel size was 316×316×100 μm. The scanning
duration was 15 seconds. In the following, intensities are expressed in Hounsfield units (HU).
Most of the image processing was realized with the ImageJ software (Rasband, 1997-2014).
Due to the chamber manipulation during the experiment and displacement of the sample
between scans, image registration was first done to ensure spatial consistency between the
different images with the Align3 TP plugin (Parker, 2012). We cropped the images to exclude
non-soil areas, and we rescaled the images to get isotropic voxels of 316 $\mu m$ . The noise was
reduced by using a bilateral filter, and edges were enhanced with an unsharp mask (Schlüter
et al., 2014). The air phase and the water phase were both separated from the soil matrix and
gravels by using the watershed segmentation method. This method has previously been
successfully used to segment images of soils (Schlüter et al., 2014). A majority filter with a
3×3×3 kernel was applied to remove very small air-filled and water-filled pores which can be
seen as noise. We finally removed manually the signal of the two tensiometers. The procedure
used to segment the air phase and the water phase gave satisfactory results (Fig. 2).
Visualization of the air-filled and water-filled pore network was done with the ImageJ plugin
3-D Viewer (Schmid et al., 2010).
The volume of air-filled and water-filled macropores was estimated with the BoneJ plugin
(Doube et al., 2010), and the Euler number was calculated considering 26-connectivity with
the C library QuantIm v.4 (Vogel, 2008), on the segmented images. The Euler number
characterizes the connectivity of the air-filled pore space (Vogel et al., 2010). When the Euler
number is positive, the pore network is classified as unconnected, whereas it is connected
when the Euler number is negative. The volume of air-filled macropores and Euler number
were calculated on the total air-filled pores identified, and the air-filled pores connected to the
soil surface only, to evaluate the pore network contributing to $N_2\mathrm{O}$ emissions. We estimated
the relative gas diffusion coefficients $D_S/D_0$ from the segmented air-filled pore space with

- QuantIm v.4 (Vogel, 2008), as already done by Deurer et al. (2009) and Vogel et al. (2002). The gas diffusion was modeled by using the Fick's law of diffusion in 3-D, solved by explicit finite differences. Throughout the simulation, the gas concentration at the bottom of the soil sample was fixed at a constant value, and the gas concentration at the top was set to zero. We calculated  $D_S/D_0$  on subsamples of increasing thickness from the soil surface (adding 10
  - 3 Results

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

## 3.1 Soil water content and soil water potential evolution

pixels at the bottom of the given subsample).

During the drying phase, the WFPS measured with the MSO system ranged between 85% and 79% at C1, and between 83% and 79% at C2. The soil matric potential was above 0 cm for the two wetting cycles for the –4 cm depth tensiometer, whereas it was slightly under 0 cm for the –2 cm depth tensiometer at C2 (Fig. 3). Saturation was thus slightly lower during C2. The matric potential showed a plateau at the C2 wetting phase, reached in approximately 4.5 h after the beginning of the C2 wetting phase. During the drying phase, the matric potential decreased linearly, immediately after activating the vacuum pump, to reach –56 cm water column at C1 and –67 cm water column at C2. The decrease of the matric potential was slightly faster at C2 than at C1 (mean decrease of –8.8 cm h<sup>-1</sup> at C1, and –9.5 cm h<sup>-1</sup> at C2).

#### 3.2 Dynamics of the N<sub>2</sub>O and CO<sub>2</sub> fluxes

Emissions were lower during C2 than during C1, both for the wetting and the drying phases, with the maximum  $N_2O$  flux being 55.1 mg N m<sup>-2</sup> d<sup>-1</sup> at C1, and 19.1 mg N m<sup>-2</sup> d<sup>-1</sup> at C2 (Fig. 3). Nitrous oxide fluxes were measured to be 9.4 and 0.1 mg N m<sup>-2</sup> d<sup>-1</sup> at the end of the C1 and C2 wetting phase, respectively. In comparison, they ranged between 0 and 2.6 mg N m<sup>-2</sup> d<sup>-1</sup> in the field measurements of Gu et al. (2011) on the same study site. Nitrous oxide

fluxes increased quickly during the drying phase to reach a peak approximately 5.5 h after the beginning of the soil drying at C1, and 4.5 h at C2. Peaks occurred at a mean matric potential of –41.1 cm water column at C1, and –44.7 cm at C2, and at a WFPS of 80.2% at C1 and 80.5% at C2. The increase in the N<sub>2</sub>O fluxes was faster for C1 than for C2. The first flux measurement of C1 was especially high (38.2 mg N m<sup>-2</sup> d<sup>-1</sup>) compared to the following measurements. At C2, the fluxes measured at the beginning of the drying phase increased more slowly, with fluxes between 3.3 and 3.9 mg N m<sup>-2</sup> d<sup>-1</sup> for the three first measurements. Carbon dioxide fluxes were higher at C2 than at C1 at the end of the wetting phase (50.4 mg CO<sub>2</sub> m<sup>-2</sup> d<sup>-1</sup> at C1, and 164.1 mg CO<sub>2</sub> m<sup>-2</sup> d<sup>-1</sup> at C2). An opposite trend was observed during the drying phase: CO<sub>2</sub> fluxes were higher at C1 than at C2 (108.3 mg CO<sub>2</sub> m<sup>-2</sup> d<sup>-1</sup> at C1, and 76.1 mg CO<sub>2</sub> m<sup>-2</sup> d<sup>-1</sup> at C2). Soil pH at the end of the two wetting-drying cycles was 5.9.

## 3.3 Characterization of the pore network

Four components could be identified, both visually and in the histograms of each image: air phase, water phase, soil matrix, and gravels (Fig. 4 and 5). We define the soil matrix as the solid phase and pores with a size lower than the image resolution. Histograms appeared to be unimodal, with the mode corresponding to the soil matrix, because the air-filled and water-filled porosities represented only a small fraction of the soil sample volume (Fig. 4a and 4b). A small peak near the pure air intensity value (–1024 HU) could be identified for the drying phase, and a small peak near the pure water intensity value (0 HU) could be identified for the wetting phase (Fig. 4c and 4d). Less water voxels and more air voxels were identified at C2 than at C1 during the wetting phase, showing that the water saturation was lower at C2 (Fig. 4c and 4d).

and at the end of the drying phase for C1 and C2 is given in Fig. 5. Cylindrical pores,

probably earthworm burrows and root channels (of which one major root channel of
approximately 9 mm diameter), as well as smaller pores attributed to inter-aggregate voids are
visible. As expected, air-filled pores appeared to be more numerous at the end of the drying
phase than at the end of the wetting phase. A high volume of pore remained not saturated
during the experiment.
Most of the indicators calculated from the segmented images were highly correlated, except
the Euler number and $D_{\rm S}/D_0$ (Table 1). Indeed, largest pores highly contributed to the
porosity, but relatively little to Euler number (Vogel et al., 2002), and $D_S/D_0$ includes
additional information about the tortuosity. The air-filled porosity identified ranged between
0.029 and 0.035 cm <sup>3</sup> cm <sup>-3</sup> at C1, and between 0.023 and 0.035 cm <sup>3</sup> cm <sup>-3</sup> at C2. In the driest
scan of C2, where the maximum air-filled pore volume has been identified, this air-filled
porosity is equivalent to 16% of the real air-filled porosity at a pressure of -100 hPa, or 7.5%
of the total porosity (0.46 cm <sup>3</sup> cm <sup>-3</sup> ). For the total core volume, time-evolution of the air-
filled pore volume showed a rapid rise from the beginning to 1 h after the soil drying, and
then the system entered a state of equilibrium (Fig. 6a). C1 and C2 followed the same trend,
but the air-filled pore volume was significantly higher at C2 than at C1 at the end of the
wetting phase, and slightly higher at C2 than at C1 during the drying phase. The volume of
water-filled pores decreased quickly in the first hour of soil drying, and remained lower at C2
than at C1 during the whole experiment (Fig. 6a). The evolution of the air-filled pores
connected to the soil surface showed the same trend as for the total core volume, except that
no more difference can be seen between C1 and C2 after 2 h of soil drying (Fig. 6c).
For the total air-filled pore volume identified, the Euler number ranged between 1319 and
1849 at C1, and between 1405 and 1713 at C2 (Fig. 6b). Thus, the Euler number was positive
during the whole experiment, meaning that the air-filled pore network was unconnected at the
resolution of the images. The Fuler number was lower at C2 than at C1 during the wetting

phase, and higher at C2 than at C1 during the drying phase. The air-filled pore connectivity
was thus better at C1 during the drying phase. The value of the Euler number tended to
decrease with soil drying. For the air-filled pores connected to the soil surface only, the Euler
number ranged between -52.5 and 17 at C1, and between -57 and 1 at C2 (Fig. 6d). A
transition between an unconnected and a connected pore network occurred in the first hour of
soil drying: the Euler number was positive at the end of the wetting phase, and negative
during the drying phase. The inherent connectivity improved then as the soil dried. The Euler
number was higher at C1 than at C2 during the whole experiment. One major pore cluster,
representing 98% of the air-filled pore volume connected to the soil surface at the end of the
two drying phases, was responsible for the negative value of the Euler number. The other
pores were smaller and had a less complicated morphology.
Simulated relative gas diffusion coefficients were null for subsamples thicker than
approximately 3 cm at C1, and 4 cm at C2, because deepest pores were poorly connected to
the soil surface. Thus, only the upper part of the soil sample could participate to the fast $N_2\mathrm{O}$
transport to the soil surface in the gaseous phase. The evolution with time of the gas diffusion
coefficient of a 3-cm-thick subsample is given in Fig. 7. Absolute values of $D_{\rm S}/D_0$ ranged
between 0.000 and 0.009 at C1, and between 0.003 and 0.005 at C2. They were higher at C2
than at C1, except for the first measurement of the C1 drying phase. Relative gas diffusion
coefficients increased quickly after the beginning of the soil drying at C1, and then showed
lower values. This peak at C1 was concomitant with a fast increase of the $N_2\mathrm{O}$ flux. The
increase with soil drying was slower at C2 than at C1. Trends were similar for the estimation
of $D_{\rm S}/D_0$ on thinner subsamples (data not shown).

# 4 Discussion

# 4.1 The use of X-ray computed tomography for greenhouse gas emission studies

The experiment of the present study appeared as the first report of coupling between soil
imaging, greenhouse gas flux measurements, and hydric control measured on the same
sample. The use of X-ray computed tomography allowed identifying spatially the water and
gas phases in the macropores, and thus determining the air-filled pore volume of these
macropores at successive moments during the soil drying. At the scanner resolution, only 16%
of the real air-filled porosity was identified, and the rest remained unresolved. Indeed, we
used a large sample, with a size typical of that used to determine soil hydraulic properties, to
approach the representative elementary volume of the soil. The pixel size was thus coarse,
approximately $300~\mu m$ . With such a resolution, only macropores are unequivocally
recognized, i.e., pores $\geq$ 300 $\mu m$ with the nomenclature of Jarvis (2007). According to Young-
Laplace law (assuming 0° degree contact angle, interfacial tension for air-water and spherical
interfaces), these macropores are expected to drain at a water potential of -10 cm.
Identifying a higher range of pore sizes would have been informative since macropores
participate to N <sub>2</sub> O transport, whereas N <sub>2</sub> O production rather occurs in fine pores of the matrix
domain (Heincke and Kaupenjohann, 1999). However, such a coarse resolution has
successfully been used in previous studies to link soil structure and gas diffusion. By using X-
ray computed tomography at a resolution of approximately 500 μm, Katuwal et al. (2014)
observed a high positive correlation between air permeability and the air-filled macroporosity
identified in their images. Deurer et al. (2009) explained a major part of the variability of the
gas diffusion coefficients by the air-filled porosity and connectivity of pores $\geq 300~\mu m$
identified with imaging. In the present study, despite the significant fraction of the unresolved
pores which were air-filled at the end of the two drying cycles, coarse-resolution X-ray
computed tomography can be used to infer N <sub>2</sub> O transport functioning. We also succeeded in

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

identifying differences in the soil moisture between the two wetting-drying cycles. This difference was consistent with the other parameters recorded, i.e., matric potential and WFPS, and allowed inferring differences in anoxia level in the soil profile between C1 and C2. Relative, instead of absolute, comparisons between the two wetting-drying cycles could thus be performed.

### 4.2 Nitrous oxide emissions and pore connectivity

After 3 days of water saturation, soil drying down to -45 cm water column induced maximum N<sub>2</sub>O fluxes. This result has been previously observed by Rabot et al. (2014). They hypothesized that the gas diffusion coefficient increased as the soil dried and allowed the release of the N<sub>2</sub>O previously entrapped during the wetting phase in the pore space or in the soil solution. Nitrous oxide entrapment in soils at high WFPS has already been highlighted in laboratory experiments (Clough et al., 1998; McCarty et al., 1999; Weier et al., 1993). In this new study, supplementary information about the soil structure was obtained and we were able to measure an increase of the air-filled macropores connected to the soil surface as the soil dried. The air-filled pore network connected to the soil surface was described as well interconnected during the drying phase. Fast N<sub>2</sub>O transport in the gaseous phase could occur from the soil upper part connected to the atmosphere during the drying phase, where some biological hotspots could be active (Ball et al., 2008; van der Weerden et al., 2012). The porous network was probably also connected by pores of a size lower than the one recorded by the X-ray scanner, which represent approximately 85% of the air-filled pore space at a pressure of -100 hPa. The observed increase of the air-filled pore volume connected to the soil surface, pore connectivity, and relative coefficient of gas diffusion with soil drying favors the hypothesis of Rabot et al. (2014), stating that entrapped N<sub>2</sub>O was released during the drying phase.

By considering the whole pore volume, the pore network was classified as unconnected during the experiment. Firstly, given that the value of the Euler number depends on the size of the lower pore which can be resolved (Vogel et al., 2010), the soil sample may have been connected by unresolved air-filled pores. With a coarse-resolution scanner, we underestimate the connectivity of the soil sample. Secondly, the Euler number is a metrics highly affected by isolated voxels (Renard and Allard, 2013), like unconnected structural pores or thresholding artifacts, leading to highly positive values. Katuwal et al. (2014) observed that the Euler number was not a good measure of macropore connectivity to compare soil samples. Evolution of the Euler number for the whole identified pore volume is thus difficult to interpret, especially as a large fraction of the pore space remained unresolved. We favor the use of the Euler number for the pores connected to the soil surface, which, by construction, includes less isolated pores. Despite a high computational cost, the estimation of  $D_S/D_0$  from the segmented pore network appeared to better describe N<sub>2</sub>O transport, by showing an evolution similar to that of N<sub>2</sub>O fluxes: a fast increase at C1 and a slow increase at C2. The relative gas diffusion coefficient provided comprehensive information, by taking into account the pore network connectivity and tortuosity, and was less affected by isolated voxels.

#### 4.3 Intensity of nitrous oxide emissions

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

By comparing the two wetting and drying cycles, differences in the amount of  $N_2O$  emitted were observed. Emissions were lower at C2 than at C1 both during the wetting and the drying phases. A lower water content at C2 may have been responsible for the lower  $N_2O$  production during the C2 wetting phase. Moreover, the higher connectivity and relative gas diffusion coefficient at C2 during the wetting phase caused lower  $N_2O$  entrapment in soil, and could also explain the lower  $N_2O$  release during the C2 drying phase. Balaine et al. (2013) suggested that  $N_2O$  emissions were low for  $D_8/D_0 < 0.006$  in their experiment on repacked soil samples at a hydric steady-state, because  $N_2O$  was entrapped in the soil and because the

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

reduction of N<sub>2</sub>O into N<sub>2</sub> was high. The observations in our present study support these findings, as we estimated values of  $D_S/D_0 < 0.006$  during the wetting phase, and we observed N<sub>2</sub>O entrapment. Nitrous oxide reduction into N<sub>2</sub> is expected to occur two or three days after the water saturation of a soil sample (Letey et al., 1980). Nitrous oxide consumption probably occurred in the present study during the wetting phase, as WFPS > 90% favors this reaction (Ruser et al., 2006). Small differences in WFPS between the wetting phases of C1 and C2 could have caused differences in N<sub>2</sub>O consumption. In the literature, reduced N<sub>2</sub>O production after a second wetting and drying cycle has also been explained by the C and N dynamics in relation to the microbial dynamics activity (Fierer and Schimel, 2002; Mikha et al., 2005; Muhr et al., 2008). In our study, nitrate was supplied in excess during the wetting phase of each wetting-drying cycle, so nitrate was supposed not to be limiting at the beginning of each wetting-drying phase. On the contrary, the carbon dynamics can be implicated in the lower emissions at C2. A shortage of C after a first wetting-drying cycle may have consumed easily available C substrates (Fierer and Schimel, 2002), and/or less C substrates may have been exposed to microbial consumption at C2, by the physical disruption of soil aggregates during the wetting-drying cycles (Denef et al., 2001).

#### 4.4 Timing of nitrous oxide emissions

In addition to the differences in terms of intensities of  $N_2O$  emissions between the two wetting and drying cycles, differences in the timing of the  $N_2O$  peaks were also observed. The matric potential appeared to be a good indicator of the timing of  $N_2O$  emissions, as already shown by Castellano et al. (2010), because the matric potential defines the diameter of the water-filled pores. We found that maximum  $N_2O$  fluxes were reached at approximately –45 cm water column, that is to say when pores with diameter > 66  $\mu$ m were drained. This is consistent with the experiment of Castellano et al. (2010), who observed in their free drainage experiment that  $N_2O$  peaks occurred when pores with diameter > 80  $\mu$ m were drained. In the experiment

of Balaine et al. (2013),  $N_2O$  peaks were observed when pores with diameter > 197 and > 57  $\mu$ m were drained, in soils repacked at bulk densities 1.1 and 1.5 g cm<sup>-3</sup>, respectively.

The timing can also be compared between the two wetting-drying cycles. In our study, N<sub>2</sub>O fluxes were very high soon after the beginning of the C1 drying phase contrary to C2. Indeed, less N<sub>2</sub>O may have been produced during the C2 wetting phase, leading to a lower gas concentration gradient between the soil surface and the atmosphere, and thus to a slower gas diffusion. Moreover, the lower rate of increase at C2 than at C1 of the air-filled pore volume, connectivity, and relative gas diffusion coefficient, at the beginning of the drying phase, could also explain the slower N<sub>2</sub>O emissions at the beginning of the C2 drying phase. These variables were highly correlated, so only one of them could have been computed. The volume of air-filled pores and the Euler number of pores connected to the soil surface were easily calculated, but the relative gas diffusion coefficient appeared to be more efficient to describe the timing of N<sub>2</sub>O emissions.

#### Conclusion

We hypothesized that introducing dynamic indicators of the soil structure could enhance our understanding of the dynamic nature of N<sub>2</sub>O emissions by soils. The experiment performed in this study was intended to demonstrate the ability of a coupling between coarse-resolution X-ray computed tomography, hydric control and N<sub>2</sub>O flux measurements, to better describe N<sub>2</sub>O transport in soils. X-ray computed tomography is a rapid and non-destructive method, which allowed measuring an evolution of the air phase volume, pore connectivity, and estimating the relative gas diffusion coefficient during successive wetting-drying cycles on the same soil sample. Contrary to the use of other characterization techniques (e.g., measurements of the gas diffusion coefficient with the one-chamber method), the hydric status of the soil has not

been m	odified	by	supplementary	wetting-drying	cycles,	and	$N_2O$	entrapment	has	not	been
disrupte	ed.										

We were able to measure an increase of the volume of the air phase connected to the soil surface, and an increase of the pore connectivity and gas diffusion coefficient as the soil dried. We used the Euler number as an indicator of the connectivity of the gas phase. Because this metrics is highly affected by isolated pores, we based our interpretations on the Euler number calculated for the pore space connected to the soil surface, rather than for the whole pore space identified with imaging. Nitrous oxide emissions were lower in terms of intensity and speed during the second drying cycle. Differences in the intensity of N<sub>2</sub>O emissions were attributed to differences in the water saturation, air-phase connectivity, and relative gas diffusion coefficient, which led to more or less N<sub>2</sub>O production, consumption, and entrapment in soil. The speed of the N<sub>2</sub>O release at the beginning of the drying phase depended on the rate of increase of the air-filled pore volume, connectivity, and was especially well described by the relative gas diffusion coefficient. Parameters of the soil structure were not able to explain completely the intensity of N<sub>2</sub>O emissions during drying, as N<sub>2</sub>O production and consumption factors modified the N<sub>2</sub>O concentration gradient between the soil and the atmosphere.

The soil structure can be seen as a factor of the N<sub>2</sub>O flux intensity because the pore size controls N<sub>2</sub>O production by providing a favorable microbial habitat (i.e., aerobic status, substrate availability, water potential), and because the pore tortuosity and connectivity to the soil surface controls N<sub>2</sub>O emission. This study highlighted the need to find and measure dynamic indicators of the soil structure, to enhance our understanding of the dynamic nature of N<sub>2</sub>O emissions by soils. The results presented here are an illustration based on one soil sample, but the methodology is widely applicable. Even if imaging with a coarse scanner

415	resolution provided valuable data, imaging techniques at a finer spatial resolution, able to
416	identify pores with diameter of approximately 50 μm, would allow refining these results.

# Acknowledgements

We are grateful to D. Colosse, P. Courtemanche, and G. Giot for their technical help in the
experimental design and/or field sampling. We also thank S. Sammartino (INRA, UMR
EMMAH) for help with the image analysis. CT-scan imaging was graciously performed by
the CIRE platform (INRA Val de Loire, site de Tours, UMR PRC), and carbon and nitrogen
analyses were graciously performed by the SAS Laboratoire. This work was supported by a
Conseil Général du Loiret grant, by the Spatioflux program funded by the Région Centre,
FEDER, INRA and BRGM, and by the Labex VOLTAIRE (ANR-10-LABX-100-01).

References

426	Balaine, N., T.J. Clough, M.H. Beare, S.M. Thomas, E.D. Meenken, and J.G. Ross. 2013
427	Changes in relative gas diffusivity explain soil nitrous oxide flux dynamics. Soil Sci
428	Soc. Am. J. 77:1496–1505.
429	Ball, B.C. 2013. Soil structure and greenhouse gas emissions: A synthesis of 20 years of
430	experimentation. Eur. J. Soil Sci. 64:357–373.
431	Ball, B.C., I. Crichton, and G.W. Horgan. 2008. Dynamics of upward and downward N <sub>2</sub> O and
432	CO <sub>2</sub> fluxes in ploughed or no-tilled soils in relation to water-filled pore space
433	compaction and crop presence. Soil Tillage Res. 101:20–30.
434	Butterbach-Bahl, K., E.M. Baggs, M. Dannenmann, R. Kiese, and S. Zechmeister-
435	Boltenstern. 2013. Nitrous oxide emissions from soils: How well do we understand the
436	processes and their controls? Philos. Trans. R. Soc. B 368.
437	Castellano, M.J., J.P. Schmidt, J.P. Kaye, C. Walker, C.B. Graham, H. Lin, et al. 2010
438	Hydrological and biogeochemical controls on the timing and magnitude of nitrous
439	oxide flux across an agricultural landscape. Glob. Change Biol. 16:2711–2720.
440	Ciais, P., C. Sabine, G. Bala, L. Bopp, V. Brovkin, J. Canadell, et al. 2013. Carbon and other
441	biogeochemical cycles. In: Stocker, T.F., D. Qin, G.K. Plattner, M. Tignor, S.K. Allen
442	J. Boschung, et al., editors, Climate change 2013: The physical science basis
443	Contribution of working group I to the fifth assessment report of the
444	intergovernmental panel on climate change. Cambridge University Press, Cambridge
445	United Kingdom and New York, NY, USA. p. 465-570.
446	Clough, T.J., S.C. Jarvis, E.R. Dixon, R.J. Stevens, R.J. Laughlin, and D.J. Hatch. 1998
447	Carbon induced subsoil denitrification of <sup>15</sup> N-labelled nitrate in 1 m deep soil
448	columns. Soil Biol. Biochem. 31:31–41.

449	Clough, T.J., R.R. Sherlock, and D.E. Rolston. 2005. A review of the movement and fate of
450	N <sub>2</sub> O in the subsoil. Nutr. Cycl. Agroecosyst. 72:3–11.
451	Denef, K., J. Six, H. Bossuyt, S.D. Frey, E.T. Elliott, R. Merckx, et al. 2001. Influence of dry-
452	wet cycles on the interrelationship between aggregate, particulate organic matter, and
453	microbial community dynamics. Soil Biol. Biochem. 33:1599–1611.
454	Deurer, M., D. Grinev, I. Young, B.E. Clothier, and K. Müller. 2009. The impact of soil
455	carbon management on soil macropore structure: A comparison of two apple orchard
456	systems in New Zealand. Eur. J. Soil Sci. 60:945–955.
457	Doube, M., M.M. Klosowski, I. Arganda-Carreras, F.P. Cordelières, R.P. Dougherty, J.S.
458	Jackson, et al. 2010. BoneJ: Free and extensible bone image analysis in ImageJ. Bone
459	47:1076–1079.
460	Fierer, N., and J.P. Schimel. 2002. Effects of drying-rewetting frequency on soil carbon and
461	nitrogen transformations. Soil Biol. Biochem. 34:777–787.
462	Groffman, P.M., and J.M. Tiedje. 1988. Denitrification hysteresis during wetting and drying
463	cycles in soil. Soil Sci. Soc. Am. J. 52:1626–1629.
464	Gu, J.X., B. Nicoullaud, P. Rochette, D.J. Pennock, C. Hénault, P. Cellier, et al. 2011. Effect
465	of topography on nitrous oxide emissions from winter wheat fields in Central France.
466	Environ. Pollut. 159:3149–3155.
467	Guo, X.B., C.F. Drury, X.M. Yang, W.D. Reynolds, and R.Q. Fan. 2014. The extent of soil
468	drying and rewetting affects nitrous oxide emissions, denitrification, and nitrogen
469	mineralization. Soil Sci. Soc. Am. J. 78:194–204.
470	Heincke, M., and M. Kaupenjohann. 1999. Effects of soil solution on the dynamics of $N_2\mathrm{O}$
471	emissions: A review. Nutr. Cycl. Agroecosyst. 55:133-157.

472	Hénault, C., and J.C. Germon. 2000. NEMIS, a predictive model of denitrification on the field
473	scale. Eur. J. Soil Sci. 51:257–270.
474	Jarvis, N.J. 2007. A review of non-equilibrium water flow and solute transport in soil
475	macropores: Principles, controlling factors and consequences for water quality. Eur. J.
476	Soil Sci. 58:523–546.
477	Kasteel, R., H.J. Vogel, and K. Roth. 2000. From local hydraulic properties to effective
478	transport in soil. Eur. J. Soil Sci. 51:81–91.
479	Katuwal, S., T. Norgaard, P. Moldrup, M. Lamandé, D. Wildenschild, and L.W. de Jonge.
480	2015. Linking air and water transport in intact soils to macropore characteristics
481	inferred from X-ray computed tomography. Geoderma 237–238:9–20.
482	Khalil, M.A.K., R.A. Rasmussen, and M.J. Shearer. 2002. Atmospheric nitrous oxide:
483	Patterns of global change during recent decades and centuries. Chemosphere 47:807-
484	821.
485	Letey, J., N. Valoras, A. Hadas, and D.D. Focht. 1980. Effect of air-filled porosity, nitrate
486	concentration, and time on the ratio of $N_2 O/N_2$ evolution during denitrification. J.
487	Environ. Qual. 9:227–231.
488	Mangalassery, S., S. Sjögersten, D.L. Sparkes, C.J. Sturrock, J. Craigon, and S.J. Mooney.
489	2014. To what extent can zero tillage lead to a reduction in greenhouse gas emissions
490	from temperate soils? Sci. Rep. 4, 4586.
491	Mangalassery, S., S. Sjögersten, D.L. Sparkes, C.J. Sturrock, and S.J. Mooney. 2013. The
492	effect of soil aggregate size on pore structure and its consequence on emission of
493	greenhouse gases. Soil Tillage Res. 132:39-46.

494	McCarty, G.W., D.R. Shelton, and A.M. Sadeghi. 1999. Influence of air porosity on					
495	distribution of gases in soil under assay for denitrification. Biol. Fert. Soils 30:173-					
496	178.					
497	Mikha, M.M., C.W. Rice, and G.A. Milliken. 2005. Carbon and nitrogen mineralization as					
498	affected by drying and wetting cycles. Soil Biol. Biochem. 37:339–347.					
499	Muhr, J., S.D. Goldberg, W. Borken, and G. Gebauer. 2008. Repeated drying-rewetting cycles					
500	and their effects on the emission of CO2, N2O, NO, and CH4 in a forest soil. J. Plant					
501	Nutr. Soil Sci. 171:719–728.					
502	Naveed, M., S. Hamamoto, K. Kawamoto, T. Sakaki., M. Takahashi, T. Komatsu, et al. 2013.					
503	Correlating gas transport parameters and X-ray computed tomography measurements					
504	in porous media. Soil Sci. 178:60–68.					
505	Parker, J.A. 2012. Stack Alignment (Align3_TP).					
506	http://www.med.harvard.edu/jpnm/ij/plugins/Align3TP.html.					
507	Rabot, E., C. Hénault, and I. Cousin. 2014. Temporal variability of nitrous oxide emissions by					
508	soils as affected by hydric history. Soil Sci. Soc. Am. J. 78:434-444.					
509	Rasband, W.S. 1997-2014. ImageJ. U.S. National Institutes of Health, Bethesda, Maryland,					
510	USA, http://imagej.nih.gov/ij.					
511	Ravishankara, A.R., J.S. Daniel, and R.W. Portmann. 2009. Nitrous oxide (N2O): The					
512	dominant ozone-depleting substance emitted in the 21st century. Science 326:123–125.					
513	Renard, P., and D. Allard. 2013. Connectivity metrics for subsurface flow and transport. Adv.					
514	Water Resour. 51:168–196.					

515	Ruser, R., H. Flessa, R. Russow, G. Schmidt, F. Buegger, and J.C. Munch. 2006. Emission of				
516	N <sub>2</sub> O, N <sub>2</sub> and CO <sub>2</sub> from soil fertilized with nitrate: Effect of compaction, soil moisture				
517	and rewetting. Soil Biol. Biochem. 38:263–274.				
518	Robertson, G.P. 1989. Nitrification and denitrification in humid tropical ecosystems: Potential				
519	controls on nitrogen retention. In: J. Proctor, editor, Mineral nutrients in tropical forest				
520	and savanna ecosystems. Blackwell Science, Oxford, U.K. p. 55-69.				
521	Sammartino, S., E. Michel, and Y. Capowiez. 2012. A novel method to visualize and				
522	characterize preferential flow in undisturbed soil cores by using multislice helical CT.				
523	Vadose Zone J. 11:86–98.				
524	Sanchez-Martin, L., A. Sanz-Cobena, A. Meijide, M. Quemada, and A. Vallejo. 2010. The				
525	importance of the fallow period for N <sub>2</sub> O and CH <sub>4</sub> fluxes and nitrate leaching in a				
526	Mediterranean irrigated agroecosystem. Eur. J. Soil Sci. 61:710–720.				
527	Schjønning, P., M. Lamandé, F.E. Berisso, A. Simojoki, L. Alakukku, and R.R. Andreasen.				
528	2013. Gas diffusion, non-darcy air permeability, and computed tomography images of				
529	a clay subsoil affected by compaction. Soil Sci. Soc. Am. J. 77:1977-1990.				
530	Schlüter, S., A. Sheppard, K. Brown, and D. Wildenschild. 2014. Image processing of				
531	multiphase images obtained via X-ray microtomography: A review. Water Resour.				
532	Res. 50:3615–3639.				
533	Schlüter, S., U. Weller, and H.J. Vogel. 2011. Soil-structure development including seasonal				
534	dynamics in a long-term fertilization experiment. J. Plant Nutr. Soil Sci. 174:395–403.				
535	Schmid, B., J. Schindelin, A. Cardona, M. Longair, and M. Heisenberg. 2010. A high-level				
536	3D visualization API for Java and ImageJ. BMC Bioinformatics 11.				
537	Sexstone, A.J., T.B. Parkin, and J.M. Tiedje. 1985. Temporal response of soil denitrification				
538	rates to rainfall and irrigation. Soil Sci. Soc. Am. J. 49:99-103.				

539	Smith, K.A. 1980. A model of the extent of anaerobic zones in aggregated soils, and its
540	potential application to estimates of denitrification. J. Soil Sci. 31:263–277.
541	van der Weerden, T.J., F.M. Kelliher, and C.A.M. de Klein. 2012. Influence of pore size
542	distribution and soil water content on nitrous oxide emissions. Soil Res. 50:125-135.
543	Vogel, H.J. 2008. QuantIm: C/C++ library for scientific image processing. Helmholtz Center
544	for Environmental Research, Halle, Germany.
545	Vogel, H.J, I. Cousin, and K. Roth. 2002. Quantification of pore structure and gas diffusion as
546	function of scale. Eur. J. Soil Sci. 53:465–473.
547	Vogel, H.J., U. Weller, and S. Schlüter. 2010. Quantification of soil structure based on
548	Minkowski functions. Comput. Geosci. 36:1236–1245.
549	Weier, K.L., J.W. Doran, J.F. Power, and D.T. Walters. 1993. Denitrification and the
550	dinitrogen/nitrous oxide ratio as affected by soil water, available carbon, and nitrate.
551	Soil Sci. Soc. Am. J. 57:66–72.
552	Weihermüller, L., J.A. Huisman, A. Graf, M. Herbst, and J.M. Sequaris. 2009. Multistep
553	outflow experiments to determine soil physical and carbon dioxide production
554	parameters. Vadose Zone J. 8:772–782.
555	Wildenschild, D., J.W. Hopmans, M.L. Rivers, and A.J.R. Kent. 2005. Quantitative analysis
556	of flow processes in a sand using synchrotron-based X-ray microtomography. Vadose
557	Zone J. 4:112–126.
558	Wollersheim, R., G. Trolldenier, and H. Beringer. 1987. Effect of bulk density and soil water
559	tension on denitrification in the rhizosphere of spring wheat (Triticum vulgare). Biol.
560	Fert. Soils 5:181–187.

561	World Meteorological Organization. 2007. Scientific assessment of ozone depletion: 2006,
562	global ozone research and monitoring project. Global Ozone Res. Monit. Project Rep.
563	50. World Meteorol. Organ., Geneva



	_
Figuro	captions
riguie	Capuons

- Fig. 1. Schematic overview of the multistep outflow system for hydric control and nitrous
- oxide measurements. Intensity values corresponding to air and water are zoomed in (c) and
- 567 (d).

- 568 Fig. 2. Example of a gray scale slice with the segmented water and air, at the end of the
- wetting phase and at the end of the drying phase.
- Fig. 3. Evolution with time of the nitrous oxide fluxes and the matric potential measured by
- 571 the two tensiometers. Gray areas represent the drying phases, and white areas the wetting
- 572 phases. C1 is the first wetting-drying cycle, and C2 is the second wetting-drying cycle.
- Fig. 4. Histograms of intensity values (16-bit), for (a) the first wetting-drying cycle, and (b)
- 574 the second wetting-drying cycle. Intensity values corresponding to air and water are zoomed
- 575 in (c) and (d).
- 576 Fig. 5. Three-dimensional distribution of the air phase (grey) and the water phase (blue) at the
- end of the wetting phase and at the end of the drying phase for the two wetting-drying cycles.
- Fig. 6. Evolution with time of (a) the air-filled and water-filled pore volume, and (b) the Euler
- number of the total pore volume, (c) the air-filled pore volume, and (d) the Euler number of
- the pores connected to the soil surface, for the first and second wetting-drying cycles. The
- zero reference time is the beginning of the drying phase.
- Fig. 7. Evolution with time of the relative gas diffusion coefficient of a 3-cm-thick subsample,
- for the first and second wetting-drying cycles. The zero reference time is the beginning of the
- 584 drying phase.

#### 585 Tables

Table 1. Pearson correlation matrix of the indicators extracted from the segmented X-ray images.

Variables	Euler number (T)	Euler number (S)	Air volume (T)	Air volume (S)	Water volume (T)	Gas diffusion coefficient (T)
Euler number (T)	1.00					_
Euler number (S)	0.44	1.00				
Air volume (T)	-0.67	-0.91	1.00			
Air volume (S)	-0.72	-0.86	0.99	1.00		
Water volume (T)	0.65	0.77	-0.94	-0.95	1.00	
Gas diffusion coefficient (T)	0.01	-0.12	0.23	0.24	-0.41	1.00

T, calculated on the total air-filled pores identified; S, calculated on the air-filled pores connected to the soil surface.




Fig. 1. Schematic overview of the multistep outflow system for hydric control and nitrous oxide measurements.




Fig. 2. Example of a gray scale slice with the segmented water and air, at the end of the wetting phase and at the end of the drying phase.




Fig. 3. Evolution with time of the nitrous oxide fluxes and the matric potential measured by the two tensiometers. Gray areas represent the drying phases, and white areas the wetting phases. C1 is the first wetting-drying cycle, and C2 is the second wetting-drying cycle.




Fig. 4. Histograms of intensity values (16-bit), for (a) the first wetting-drying cycle, and (b) the second wetting-drying cycle. Intensity values corresponding to air and water are zoomed in (c) and (d).




Fig. 5. Three-dimensional distribution of the air phase (grey) and the water phase (blue) at the end of the wetting phase and at the end of the drying phase for the two wetting-drying cycles.




Fig. 6. Evolution with time of (a) the air-filled and water-filled pore volume, and (b) the Euler number of the total pore volume, (c) the air-filled pore volume, and (d) the Euler number of the pores connected to the soil surface, for the first and second wetting-drying cycles. The zero reference time is the beginning of the drying phase.




Fig. 7. Evolution with time of the relative gas diffusion coefficient of a 3-cm-thick subsample, for the first and second wetting-drying cycles. The zero reference time is the beginning of the drying phase.