Geophysical Research Abstracts Vol. 21, EGU2019-17168, 2019 EGU General Assembly 2019 © Author(s) 2019. CC Attribution 4.0 license.



Toward accurate magma temperature determination: in situ direct emissivity measurements of phonolite Teide and Erebus volcanos

Hao Li (1), Joan Andújar (1), Aneta Slodczyk (1,2), Domingos De Sousa Meneses (2), and Bruno Scaillet (1) (1) Université d'Orléans, ISTO, UMR 7327, 45071, Orléans, France ; CNRS/INSU, ISTO, UMR 7327, 45071 Orléans, France ; BRGM, ISTO, UMR 7327, BP 36009, 45060 Orléans, France, (2) CNRS, UPR 3079 CEMHTI, 45071 Orléans Cedex 2, France

The temperature of magma is an important parameter to understand the activity of volcanos in consideration of minimize the volcano hazard. Recently, real time thermal remote sensing (such as camera IR or different instruments install on satellite) is largely used for the temperature measurements. This technology is based on measuring the infrared (IR) emitted flux of the body. However, these techniques have large uncertainties of \pm 100°C [1]. Our study is aimed at gaining new information on the radiative heat transfer of rocks, in order to improve the accuracy of magmatic temperature determination through laboratory optic measurements.

Samples from two phonolite volcanos (Erebus and Teide) have been selected for the measurements, their chemistry composition are very similar (except the percentage of FeO*, 3 wt% for Teide sample and 5 wt% for Erebus sample). We used high potential IR emissivity apparatus [2] allowing a direct non-contact in situ IR emittance measurements as a function of high temperature and in a wide spectral range. The Erebus and Teide samples were measured from room temperature up to $2000 \, \mathrm{K}$ with a CO_2 laser, both on heating and cooling; spectra were collected from $400 \, \mathrm{to} \, 8000 \, \mathrm{cm}$ -1.

Our results reveal that thermal emissivity of magmatic rock is affected by changes in composition and thermal history. The Teide sample has no significant evolution of emissivity during heating. However, the Erebus sample shows an important emissivity changes (level of 50% difference between high and low emissivity) with the temperature, pointing clearly that the emissivity is not a constant value and it can be very variable during heating and cooling.

Two cooling rates are applied on the sample during the test, fast cooling refers to volcanic bomb, and slow cooling is associate to lava flow. Erebus sample shows different emissivity with different rate of cooling.

The emissivity measurements show also the important role of the iron on the spectral response of the phonolite composition. Starting from 5 % the iron-based clusters are formed and change drastically radiative properties of the sample.

Finally, our results allowed to discuss the accuracy of Erebus lava lack temperature presented in literature.

References:

- [1] Aufaristama, M., Hoskuldsson, A., Jonsdottir, I., Ulfarsson, M., & Thordarson, T. (2018). New Insights for Detecting and Deriving Thermal Properties of Lava Flow Using Infrared Satellite during 2014–2015 Effusive Eruption at Holuhraun, Iceland. Remote Sensing, 10(2), 151. http://doi.org/10.3390/rs10010151
- [2] De Sousa Meneses, D., Melin, P., del Campo, L., Cosson, L., & Echegut, P. (2015). Apparatus for measuring the emittance of materials from far infrared to visible wavelengths in extreme conditions of temperature. Infrared Physics & Technology, 69, 96–101. http://doi.org/10.1016/j.infrared.2015.01.011