

A hillslope-scale aquifer-model to determine past agricultural legacy and future nitrate concentrations in rivers

Luca Guillaumot, Jean Marçais, Camille Vautier, Aurélie Guillou, Virginie Vergnaud, Camille Bouchez, Rémi Dupas, Patrick Durand, Jean-Raynald de Dreuzy, Luc Aquilina

▶ To cite this version:

Luca Guillaumot, Jean Marçais, Camille Vautier, Aurélie Guillou, Virginie Vergnaud, et al.. A hillslope-scale aquifer-model to determine past agricultural legacy and future nitrate concentrations in rivers. Science of the Total Environment, 2021, 800, pp.149216. 10.1016/j.scitotenv.2021.149216 . insu-03320536

HAL Id: insu-03320536 https://insu.hal.science/insu-03320536

Submitted on 16 Aug 2021 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

A hillslope-scale aquifer-model to determine past agricultural legacy and future nitrate concentrations in rivers



Luca Guillaumot, Jean Marçais, Camille Vautier, Aurélie Guillou, Virginie Vergnaud, Camille Bouchez, Rémi Dupas, Patrick Durand, Jean-Raynald de Dreuzy, Luc Aquilina

PII:	S0048-9697(21)04289-3
DOI:	https://doi.org/10.1016/j.scitotenv.2021.149216
Reference:	STOTEN 149216
To appear in:	Science of the Total Environment
Received date:	7 May 2021
Revised date:	16 July 2021
Accepted date:	19 July 2021

Please cite this article as: L. Guillaumot, J. Marçais, C. Vautier, et al., A hillslopescale aquifer-model to determine past agricultural legacy and future nitrate concentrations in rivers, *Science of the Total Environment* (2018), https://doi.org/10.1016/ j.scitotenv.2021.149216

This is a PDF file of an article that has undergone enhancements after acceptance, such as the addition of a cover page and metadata, and formatting for readability, but it is not yet the definitive version of record. This version will undergo additional copyediting, typesetting and review before it is published in its final form, but we are providing this version to give early visibility of the article. Please note that, during the production process, errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

© 2018 © 2021 Published by Elsevier B.V.

A hillslope-scale aquifer-model to determine past agricultural legacy and future nitrate concentrations in rivers

Luca Guillaumot^{1,2}*, Jean Marçais³, Camille Vautier¹, Aurélie Guillou^{1,4}, Virginie Vergnaud¹, Camille Bouchez¹, Rémi Dupas⁵, Patrick Durand⁵, Jean-Raynald de Dreuzy^{1,6}, Luc Aquilina¹

¹ Univ Rennes, CNRS, Géosciences Rennes, UMR 6118 35000 Rennes, France

² Water Security Research Group, Biodiversity and Natural Acources Program, International Institute for Applied Systems Analysis (IIASA), Lexenburg, Austria

³ INRAE, UR Riverly, F-69625 Ville, rbanne, France

⁴ Université Savoie Mont Blanc, Polytech-Annecy Chambéry, Le Bourget du Lac 73370, France

⁵ INRAE, Agrocampus Ouest, ¹¹M.² 1069 SAS, 35000 Rennes, France

⁶ Univ Rennes, CNRS, OSUR (Observator), des sciences de l'univers de Rennes), UMS 3343,

25700 Rennes, France

*corresponding author: guillaur ot iiasa.ac.at

1 Introduction

Intensive agriculture which has developed since the 1960's has caused eutrophication in aquatic environments (Steffen et al., 2015; Withers et al., 2014). In coastal areas, nitrogen excess led to dramatic green algae proliferations having ecosystem, sanitary and economic repercussions (Galloway et al., 2008; Kronvang et al., 2005; Ménesguen and Salommon, 1988). These problems have raised public awareness and led to regulation s to reduce the nutrient load in water bodies (Boers, 1996; European Comission, 1991). As a result, since the 1990's, the agricultural inputs of nitrogen have decreased in many European regions (Abbott et al., 2018; Aquilina et al., 2012; Kronvang et al., 2008; Poisvert et al., 2017). Yet, the impacts of mitigation strategies are still difficult to evaluate and even more ω predict (Withers et al., 2014). Especially, the fate of the missing nitrogen (input minus vive, export), which is either stored or removed, is uncertain and blurred by other uncertainties such as data uncertainties and the imbrications of both spatial and time scales (Breemer et al., 2002).

Nitrate concentrations in rivers do not only depend on the anthropic nitrogen inputs, but also on natural processes that occur within catchments (Chen et al., 2018; Małoszewski and Zuber, 1982) such as the relative importance of overland flows, shallower groundwater flows and deeper groundwater rlows or such as autotrophic and heterotrophic denitrification in soils, rivers and aquifers. The rate and dynamics of the excess of nitrogen delivery to the water courses depends on agricultural management and soil processes. Nitrogen excess can be stored in soils and aquifers yielding a temporary retention of nitrogen, the so-called nitrogen legacy (Dupas et al., 2020; Ehrhardt et al., 2019; Hrachowitz et al., 2015; Van Meter et al., 2017, 2016). Indeed, aquifers exert control over the long-term nitrogen concentration in rivers (Aquilina et al., 2012; Hamilton, 2012; Meals et al., 2010) because groundwater can transit several decades before

discharging into the river (Ayraud et al., 2008; Gleeson et al., 2016; Kolbe et al., 2016; Marçais et al., 2018). At a global scale, an important part of river discharge comes from groundwater. In regions with a crystalline geology, such as French Brittany, most river water originates from groundwater systems, with transit times ranging from days to decades. Beside the long-term effect of nitrate transfer with groundwater, the nitrate concentration in rivers is also impacted by a fraction of young water. Indeed, rivers are globally fed by a substantial proportion of water less than three months old (Benettin et al., 2017; Jasechko et al., 2016), which mixes with older groundwater. Young waters either runs off to the river without infiltrating into the aquifer or emerges from saturated shallow horizons (Marcais et al., 2017). This fraction of young water drives a short-term, typically seasonal, variability in nume concentrations in rivers (Martin et al., 2004; Molénat et al., 2002; Van Der Velde e. al. 2010a). Finally, nitrate concentrations in rivers are also controlled by the microvial denitrification (Knowles, 1982), which has the potential to reduce the total load of nite te. The denitrification occurs under anoxic conditions after oxygen consumption by aerobic microorganisms, nitrate being the second highest energy level support following oxygen. Such conditions can be found in several compartments of the catchment where oxyger is poorly available such as riparian wetlands, which remain waterlogged during a large part of the year (heterotrophic denitrification with organic matter) and in the deeper part of the saturated zone with longer and deeper flow paths (autotrophic denitrification with pyrite) (Aquilina et al., 2018; Green et al., 2016; Kolbe et al., 2019; Korom, 1992; Molénat et al., 2002; Roques et al., 2018a; Tarits et al., 2006; Van Der Velde et al., 2010b; Van Meter and Basu, 2015). Therefore, evaluating the relative effects of these functional properties of the catchment is crucial to understand the dynamics of nitrate and to predict the impacts of mitigation strategies on river quality.

The role of young water fraction, aquifer storage and denitrification remains uncertain because hydrologists can never fully quantify the groundwater contribution to surface water associated to each point of the transit time distribution (Hrachowitz et al., 2016). Moreover, the competition between transport and denitrification, commonly expressed as the Damköhler number, is known to give a functional, integrative view of the nitrate fate in catchments (Green et al., 2010; Ocampo et al., 2006a; Oldham et al., 2013; Takuya et al., 1993; Zarnetske et al., 2012). Nevertheless, the transport and denitrification properties is indamentally arise from the geological, biogeochemical and hydrological properties of the conclusionent (Pinay et al., 2015). We argue that dealing with this issues requires (1) data constraining the partitioning of groundwater transit times, (2) to define the most important catchment properties and (3) time scales that they control in the aim to (4) reproduce catchment in trate dynamics and be able to predict concentration trends.

Many studies have been performed at catchment scales to understand and predict nitrate variations in rivers and groundwater sy terms. They developed and combined different modelling approaches, inferring different representations of transit times within the catchment (Chen et al., 2018; Hrachowitz et al., 2016). Simple conceptual (or lumped) models can be used (Berghuijs and Kirchner, 2017; Fo et et al., 2015; Kirchner et al., 2000; Marçais et al., 2015). They generally represented catchments by one or several reservoirs whose water contents and associated concentrations are governed respectively by linear (or Dupuits equation) and distribution functions of transit times (going from perfect mixing assumption to more complex gamma function coupled with a degradation law). Some studies focused on the relationship between temporal variations and spatial distributions of nitrate (Martin et al., 2006; Ocampo et al., 2006a; Pinault and Pauwels, 2001) mainly at hillslope scale. Other authors implemented 2D

or 3D numerical groundwater models and computed transit time distributions and/or nitrate concentrations from the resulting flow structure (Gburek and Folmar, 1999; Kaandorp et al., 2018; Van Der Velde et al., 2010a; Wriedt and Rode, 2006). On the other hand, physically-based and spatially distributed models such as TNT2-STICS (Beaujouan et al., 2002) and INCA (Wade et al., 2002), also called mechanistic models, take into account most of the processes impacting nitrate fluxes such as water transfer in soils, crop development and the associated soil/plant nitrogen transformation. The accuracy of these models' predictions rolies on a precise knowledge on agricultural practices (in time and space), on soil properties and on the control of epistemic uncertainties resulting from the simplified conceptualization of the system and on parameter identification issues. Their hydrogeological part is generally described by simpler conceptual models.

In this paper, we investigate the controlling factors of the nitrate trends and variability in three rivers of the highly eutrophic French region of Brittany (Abbott et al., 2018; Aquilina et al., 2012; Beaujouan et al., 2001; Poissert et al., 2017). This area has been investigated for almost two decades on nitrate contamination issues (Ayraud et al., 2008; Conan et al., 2003; Fovet et al., 2015; Martin et al., 2006; Model at et al., 2002; Roques et al., 2018b; Ruiz et al., 2002) and for water resources in crystalline aquifers (Goderniaux et al., 2013; Jimenez-Martinez et al., 2013; Kolbe et al., 2016; Le Borgne et al., 2006; Leray et al., 2014; Wyns et al., 2004). We focus on the roles of sub-surface aquifers, which are strongly connected to the rivers. The catchment is represented by a single equivalent hillslope model governed by groundwater flow equation and water table interception with the surface. The vertically-resolved approach combined with a first-order degradation law allows to represent a classic water transit time stratification in the aquifer and the resulting nitrate stratification. The model is informed by long-term river data such as

streamflows and nitrate concentrations, complemented with punctual CFC-derived ages in rivers, springs and wells. This parsimonious modelling approach enables to test a wide range of values of hydrogeological and biogeochemical parameters (around 20 000 simulations for each catchment), without any assumptions on the aquifer structure. Based on the validated models, we identify the main aquifer properties controlling the nitrate dynamics in terms of hydrogeological behavior, reactivity and geological structure. We further predict future nitrate trajectories from 2015 to 2050 following two input scenarios.

2 Study area setting

The study focuses on three agricultural catements (Douron, Ris and Kerharo) located near the coast of Brittany, Western France Brittany is the first livestock region in France due to massive industrialization of its agriculture, which began in the 1960's (Deschamps et al., 2016). This led to high inputs of organic and minoral nitrogen (Dupas et al., 2018; Poisvert et al., 2017). The excess of nitrogen causes dramatic green algae proliferations in several bays during the summer season (Ménesgum and Salommon, 1988), implying damages for the coastal ecosystems and for the territor industry (Gambino, 2014). Since the 1990's, efforts have been made to reduce the agricultural nitrogen inputs, leading to a decrease in the nitrogen concentrations in rivers (Abbott et al., 2018; Aquilina et al., 2012; Poisvert et al., 2017). However, nitrogen concentrations in rivers are still elevated and many rivers have a nitrate concentration exceeding 25 mg/L (Abbott et al., 2018).



Figure 1: The Ris and the Kerharo catch. ents, located on the westernmost point of France, discharge into the bay of Douarnenez, in the Atlantic C cean. The Douron catchment, located on the north coast of Brittany, discharges into the bay of Locauirec, in the Manche.

The three agricultural catchments studied here (*Figure 1*) are discharging into bays subjected to green algae proof rations, making them representative of the regional eutrophication issue. In the three catchments, the major agricultural activity is dairy production. Land use includes maize, winter wheat and rapeseed crops in rotation with ley, as well as pastures. Catchment areas range between 30 and 38 km² (*Table 1*). The climate of the three catchments is temperate and oceanic, with precipitations relatively distributed over the year (on average 1100 mm/yr). Geologically, the studied catchments are underlain mainly by granite and shales. In Brittany, subsurface is divided into the soil layer (a few decimeters), the weathered zone (a few

meters to a few tens of meters), the fractured zone (a few tens of meters to a few hundreds of meters) and the fresh basement (Maréchal et al., 2004; Molénat et al., 2013; Mougin et al., 2008; Wyns et al., 2004). The Ris catchment, as delimited by the gauging station, (northern blue point on *Figure 1*), is mainly composed of granite. The geological map reveals regional fractures aligned to a long a NW-SE axis and some shale bodies in the downstream section (provided by the *BRGM*, French Geological Survey). The Kerharo catchment is composed of NW-SE fractures and metamorphous shales (micaschist) with pyrite found during botcholes drilling at the bedrock interface (few meters depth) (Faillat et al., 1999). The Democra catchment is composed of different granitic bodies and some metamorphous shales in the downstream section.

This subsurface structure strongly connects surface and sub-surface water flows, with many interactions between aquifers, soils and rivers (M. dir et al., 2006; Molénat et al., 2013; Ruiz et al., 2002). Estimated recharge to aquifers if or average close to 400 mm yr⁻¹ (Habets et al., 2008; Le Moigne, 2012; Quintana-Seguí et al., 2008) making the weathered horizon the main capacitive layer for water (Ayraud et al., 2008; Wyns et al., 2004). For the three catchments, the hydrogeological conceptual model is composed of a weathered capacitive layer (< 2 m depth) overlying a fractured draining layer. Surface runoff mainly occurs as saturation excess overland flow in valley bottoms where the aquifer intersects the land surface during the wet season (Ogden and Watts, 2000). Excess infiltration overland flow is generally low in Brittany as precipitations are equally distributed throughout the year. Streamwater therefore mainly consists in surface runoff, lateral transfer within the soil, and groundwater circulation in the weathered parts of the aquifer. The proportion of river water originating from the aquifer varies throughout the year, but is globally high. Previous studies in Brittany found a groundwater contribution to rivers of 55% on average (Mougin et al., 2006). By comparing estimated mean groundwater

recharge from land surface model applied over France (SURFEX platform) (Habets et al., 2008; Masson et al., 2013; Quintana-Seguí et al., 2008) with observed mean streamflow, we found a groundwater contribution to stream of 80% on average for the three studied catchments.

Table 1: Main characteristics of the Ris, Kerharo and Douron catchments. Geology is given by maps of the French Geological Survey (BRGM). Climate data (average from 1998-2018) come from the SURFEX platform. Discharge data and nitrate concentrations (average from 1998 to 2010 and from 1998 to 2015 respectively) are given by the water basin agencies. The trend in nitrate concentration in the river is obtained by a linear regression.

Property	Ris	Serharo	Douron
Area [km ²]	31	38	30
Slope [%]	5	6	6
Characteristic length [km]	1	1.1	1.1
Dominant lithology	Granite (+fault zone)	Micaschist	Granite
Precipitation [mm/yr]	1132	1072	1145
PET [mm/yr]	670	655	610
Discharge [mm/yr]	569	473	530
Mean nitrate concentration in river[mg/L]	34	32	31
Trend in nitrate concentration [mg/L/yr]	-0.46	-0.92	-0.55

3 Material and methods

3.1 Field data

3.1.1 Long term monitoring data: discharge and nitrate streamwater time series

To inform the main hydro-biogeochemical processes occurring at the catchment scale, long time series of stream discharge and nitrate concentrations observed in the three catchment rivers were gathered. First, monthly river discharge from 1998 to 2010 as presented (Figure 2). These streamflow initially collected by mea uring data were the daily river height (http://hydro.eaufrance.fr/). Average observed streamf'ow values are given on Table 1 for the 1998-2010 period. Annual discharge standard deviation, representative of the interannual streamflow variability, is on average equal to 0..7 m/yr for the three catchments to compare with the average discharge of 0.52 m/yr. Seaso, al variations are quite regular through years and influenced mainly by the low evaryoranspiration demand between November and March. Streamflow are approximately 4 10 times higher during the wet season compared to the dry season indicating a pronounced seasonality and a fast answer to recharge events (Figure 2). The strongest seasonal variab lity is found for the Kerharo catchment with streamflow ranging each year between 4 and 100 mm/month roughly. In spite of the distance between Ris and Douron catchments (80 km), they show very similar seasonal behaviors. The smaller response time for the Kerharo catchment, illustrated by recessions slope on *Figure 2*, is attributed to its geomorphological and geological features (*Table 1*) as this catchment is very close from the Ris catchment, with quite similar climate and soil occupation.



Figure 2: Observed specific streamflow normalized by c_tchn_ints area (in logarithmic scale) for the three studied catchments along the period of calibration of the model. Monthly data are derived from daily time step streamflow. Grey filled areas correspond to estimated groundwater recharge rates for the Kerharo catchment (section 2.4.1).

Secondly, monthly nitrate concentrations in rivers from 1998 to 2015 are presented (*Figure 3*). These data were in 'tia.'y collected at bi-monthly time step by local basin agencies. Average nitrate concentration in rivers is around 32 mg/L for the three catchments over the 1998-2015 period (*Table*). For all catchments, concentrations are decreasing during this period (on average -0.6 mg/L/yr), with highest decrease for the Kerharo river (-0.92 mg/L/yr). In addition, nitrate concentrations were occasionally measured between 1976 and 1984 in the Ris river (black dots on *Figure 3*). These data come from NAÏADES French data base (<u>http://www.naiades.eaufrance.fr/</u>). This data was added to the 1998-2015 nitrate monitoring datasets as they provide an interesting opportunity to assess the long-term behavior of the catchment. As highlighted by the interpolated dashed curve on *Figure 3*, based on several trends

observed in Brittany (Aquilina et al., 2012; Dupas et al., 2020, 2018; Kolbe, 2017), measured data did not cover the nitrate peak concentrations occurring between 1990 and 2000.



Figure 3: Observed nitrate concentrations in the river at the discharge stations of the three studied catchments. Initial data are at weekly time step, unless on the Ris river for the period 1976-1984 where punctual data were available (bite acts). Shaded areas corresponds to estimated recharge periods. Dashed curve extrapolates periods without data, with a maximum of concentration occurring between 1990 and 2000 in Brittan.

3.1.2 Sampling campaigns: CFCs groundwater age tracers

CFCs and nitrate concentrations were measured in boreholes, springs and rivers in the three studied catchments. Two sampling campaigns were performed, at the end of the wet season (March 2019) and at the end of the dry season (October 2019). Sampling locations are shown in *Figure 1*. For each catchment, we performed three samplings in the river and 7 to 13 samplings in springs and boreholes. The number and the location of springs and boreholes samplings were

constrained by accessibility and landlord authorization. Details about the sampling techniques used to measure CFCs are presented in the Supplementary Material.

CFCs concentrations were then converted into apparent ages through the use of a Lumped Parameter Model (Marcais et al., 2015) to be used for calibrating the solute transport parameters of the hillslope model (section 3.2.2). To do so, we assumed an a priori parametric age distribution that we convoluted with the input atmospheric CFCs concentration. Exponential distribution of transit times is compatible with 1D Boussinesq aquifer model and relevant while seasonal fluctuations do not impact significantly the mean transit time and while the aquifer saturation is limited (low young water contribution). Thus, xponential distribution is appropriate to estimate mean water transit time from CFCs san, ing in boreholes, spring and rivers considering all these points are located in convergince zones (Marçais et al., 2015), downstream of the hillslopes or subject to farmer punping. Note that CFCs in deep wells (>30m depth) consistently show very low concentrations revealing long transit times which can be modelled by gamma distribution. Indeed, when sr undwater is old (typically >60 yr considering the exponential model), the accuracy of the CFC tracers decreases. Thus, these older values will be considered as a lower boundary and will not be used in the model calibration. For each catchment, the observed mean transit time, later compared to the simulated mean transit time (τ_{TT}) , is an average between March and October CFC-derived ages of all springs and shallow boreholes. To prevent misinterpretation due to potential CFCs contamination, we only retain samplings where at least two CFCs among CFC-11, CFC-12, CFC-13 lead to similar apparent ages (Jurgens et al., 2012).

3.2 Modelling approach

The model simulates flow and nitrate transport in three aquifers over the 1955-2010 period. For the three studied catchments, hillslope models were calibrated over the 12-year period from 1998 to 2010 for streamflow and over the 10-year period from 2000 to 2010 for nitrate concentrations in river (section 3.2.3). For Ris and Kerbaro catchments, the model is extrapolated until 2015 (see Supplementary Material). Here, we present (1) recharge and nitrate inputs coming from a hydrological and nitrogen soil/plant node) (2) the hillslope aquifer model (3) the calibration method and (4) the relevant model properties.

3.2.1 Recharge and nitrogen inputs

To estimate recharge and nitrate up its over the 1955-2015 period, we merged two modeled datasets providing either nitrate and/or groundwater recharge inputs over different time scales. First, we used the TNT2-STICS model providing monthly recharge rates and nitrate concentrations in this recharge vate, over the 1997-2010 period (Beaujouan et al., 2002). This period is constrained by nitrate measures in river and the monitoring of agricultural practices. TNT2-STICS is a spate. 'I'y distributed hydrological and nitrogen model running at daily time step and taking into account several soil layers for water transfers. Crop development and the associated soil/plant nitrogen transformation are physically represented along with heterotrophic denitrification in soils and in often saturated areas like humid zones. TNT2-STICS is alimented by climate data (rainfall and potential evapotranspiration), nitrogen inputs by agriculture and crop specific parameters. To model nitrate legacy of past practices, the hillslope model is run on a longer period starting some more than 40 years before, in 1955. We combined TNT2-STICS nitrate inputs with nitrate annual surplus estimates covering the 1955-2015 period (Poisvert et

al., 2017) to retrieve monthly estimates of nitrate inputs over the 1955-1997 period and over the 2010-2015 period, except for the Douron catchment where lack of input data prevent to extend monthly nitrate inputs over the 2010-2015 period (see Supplementary Material). Thus, groundwater recharge from TNT2 constitutes the only water input to the hillslope model. Note that TNT2 already takes into account soil-groundwater exchanges using a simplified representation of the groundwater compartment. We used here the net groundwater recharge (recharge minus "excess groundwater") corresponding to more than 93 % of the river streamflow for the studied catchments (Beaujouan et al., 2002). Excess infiltration overland flow is considered negligible (section **Error! Reference source n. found.**). Finally, the hillslope-scale aquifer model restitutes this recharge to the river as ball flow, aquifer seepage and saturation excess overland flow (section 3.2.2).

Figure 4 presents the simulated nit. hte inputs to the aquifer for the three catchments from 1955 to 2015. They are given in mass per year by multiplying the monthly groundwater recharge rates by the concentrations of nitrate in the recharge. They show a strong increase from 1955 to 1990, followed by a decrease between 2000-2005 after the nitrate directive (1991). Since 2005, the trend is masked by an inter-annual variability stemming from several factors including climate and a lower decrease in agricultural inputs. The three catchments behave slightly differently as illustrated by the variability between the three curves on *Figure 4*. Differences come from land use and agricultural practices.



Figure 4: Annual nitrate mass inputs in the three studied cased ments. Values are obtained from TNT2-STICS model and are later imposed to the groundwater at lel. Note that inputs are given to the model at a monthly time step but are presented here at computer and smoothed using a moving average of three years for better visualization.

3.2.2 The 2D hillslope model

A two-dimensional hillslop model is defined for each catchment (*Figure 5*). It assumes that, at the catchment scale, the nydrological system behavior is controlled by two hillslope-scale processes, which are the groundwater flow stratification processes and the saturation-excess runoff processes coming from the water table interception with the surface (Brutsaert, 1994; Fan et al., 2019; Marçais et al., 2017; Matonse and Kroll, 2009; Troch et al., 2003). The structure of the hillslope (length and slope) is derived from averaged geomorphologic properties (*Table 1*). The bottom of the hillslope is considered horizontal. Its characteristic thickness (*E*) is defined at the most downstream point of the hillslope (*Figure 5*). Its hydraulic conductivity (*K*) and porosity (θ) are assumed uniform. The bottom, left and right boundaries are no-flow conditions (*Figure 5*).

The right boundary (upstream) corresponds to the topographic divide of the hillslope while the left boundary (downstream) corresponds to the river flowing perpendicularly to the modeled section. When the water table reaches the surface on the upper limit (blue line on *Figure 5*), groundwater seeps and directly feeds the river. With higher recharge, the seepage front moves upstream along the horizontal axis. Streamflow in the river results from the discharge of the aquifer to the river and upstream from the seepage area. Given the limited extension of the hillslope and the weekly time step of the model, seepage is assumed to be transferred without any delay to the river. Similarly, streamflows are compared withnediate river routing scheme at the outlet of the catchment given the small catchmen's size (~30 km²). Flow and nitrate transport models are implemented within the well-known `ODFLOW and MT3D software suite through the Python Flopy interface (Bakker et 21., 20.6; Bedekar et al., 2016; Harbaugh, 2005; McDonald and Harbaugh, 1984; Zheng and Wang, 1999). They are presented in details in Supplementary Material. The modelled mean transit times are computed by dividing the groundwater volume by the mean recharge. They are compared to the mean transit time derived from the CFCs (section 3.1.2). Coundwater nitrate inputs, as well as recharge rates, are provided by the TNT2-STICS model 'Lines, we only consider here nitrate transport in the aquifer, without taking into account the unsport through the soil done by TNT2-STICS. Nitrate is denitrified in the aquifer under favorable anoxic redox conditions with accessible electron donors like pyrite (Green et al., 2016; Kolbe et al., 2019; Korom, 1992; Molénat et al., 2002; Tarits et al., 2006; Van Der Velde et al., 2010a; Van Meter and Basu, 2015). Denitrification inside the aquifer is modeled by an effective first-order reaction (*equation* (1)):

$$r(\tau) = 1 - exp\left(-\frac{\tau}{\tau_{NO3}}\right) \tag{1}$$

where τ_{NO3} is the characteristic denitrification time and τ is the transit time. Most of the heterotrophic denitrification in often saturated areas such as humid zones is already implicitly taken into account in the TNT2 soil model.



Figure 5: Sketch of the 2D hillslope m_{α} del. The morphology of the hillslope is defined by its length (L) (here 1000 m), its characteristic thickness (E) (here 80 m) and the slope of its surface (here 0.05). The model is parameterized by its policy ity (θ) (here 0.05), its characteristic thickness (E) (here 80 m) and its hydraulic conductivity (\mathbf{K}) (here 4.10-6 m/s). Transit times are represented in colors on the flow lines (mean transit time is 9.6 yr). The stratification of times is classical for homogeneous hillslope models. Streamflow in the river results from the discharge of the aquifer to the river (upper left corner of the model) and upstream from it as seepage. Given the limited extension of the hillslope, seepage is assumed to be transferred without any delay to the river.

The hillslope model has four unknown parameters, which are its hydraulic conductivity (*K*) [m/s], its thickness (*E*) [m], its porosity (θ) [*without unit*] and its characteristic denitrification time (τ_{NO3}) [yr]. From these parameters, we also use a closely related indicator, the mean

saturated thickness (E_{wet}) (obtained after simulation). The transmissivity (KE_{wet}) partitions the streamflow between groundwater flows and saturation excess overland flows through the mean saturated thickness and through the mean extent of the seepage zone. The time fluctuations of the overland flows and saturated thickness are conditioned by the porosity (θ). The smaller is the porosity, the larger the fluctuations of the seepage zone among seasons. The porosity also intervenes in the mean equivalent water height (θE_{wet}) which, divided by the recharge, gives the mean transit time (τ_{TT}) (Cornaton and Perrochet, 2007; Danckwerts, 1953; Haitjema, 1995) (*equation* (2)):

$$\tau_{TT} = \frac{\theta E_{wet}}{R} \tag{2}$$

where *R* is the recharge expressed in [L/T]. Thus, ∂E_{wet} represents the groundwater volume normalized by the hillslope surface.

The characteristic denitrification time (τ_{NO_n}) influences nitrate concentrations but also will adjust itself to the aquifer volume in Field through the calibration. It therefore controls the relative importance of nitrate dilution and removal. All four parameters (K, E, θ , τ_{NO3}) are thus interdependent when calibrates' from the observed flows, CFCs-derived ages and nitrate concentrations. In-stream denitrification is tightly related to residence time in rivers and diffusion processes within the hyporheic zone (Boulton et al., 1998; Gabriel et al., 2006; Zarnetske et al., 2011). In-stream heterotrophic denitrification is considered negligible within this study because of the small residence time in the short rivers of low Strahler orders (Lefebvre et al., 2007; Montreuil et al., 2010) and the high river oxygenation (Vautier et al., 2020). Low instream denitrification might only appear during dry season and would correspond to a limited period of the year when the streamflow is very low (<10% of the annual flow). Nitrate can also be consumed by macrophyte and phytoplankton but this usually occurs in streams with higher

Strahler order where their development is favored (Durand et al., 2011). As a whole, such denitrification processes should remain low and represent a limited extent of nitrate fluxes without noticeable modifications of the results presented here.

Finally, this model is simple and parsimonious in order to be calibrated with a limited amount of data. It is a mechanistic model proposing temporally and spatially dynamic representations of saturation, subsurface flows and surface interception essential to reproduce the conditions of relatively shallow aquifers (10-100 meters) and temperate climates as it prevails in Brittany. Indeed, the wet winter season in Brittany favors high recharge rates and the development of seepage in a landscape of small slopes and limited aquifer capacities (Goderniaux et al., 2013; Kolbe et al., 2016; Meror et al., 2014). The three third-order catchments studied here are in fact made up of small slopes of average length around 1 km as determined by the transition from hillslop, to aver in a classical area-slope relation (Lague et al., 2000) (*Table 1*). They are relatively flat with mean surface slopes of 5 to 6%.

3.2.3 Calibration method

The objective function of the optimization problem was obtained as a combination of classic calibration functions or the three types of observables: streamflow time series, nitrate time series and CFC-derived mean transit times. We used the Nash-log criterion to assess the ability of the model to reproduce monthly streamflow time series (1998-2010, *Figure 2*). Nash-log equilibrates the relative influence of the low and high flows and is particularly adapted to focus on groundwater flows (Gupta et al., 2009). The monthly nitrate concentrations in rivers (2000-2010, *Figure 3*) are compared to the simulated data using the root mean square error (Gupta et al., 2009) criterion normalized by the standard deviation of observations (*nRMSE*). To focus the calibration on the long-term trend, both observed and simulated monthly-river

concentrations are smoothed out by keeping only the best linear function according to a leastsquares fit on the data. Punctual nitrate concentrations measured between 1976 and 1984 in the Ris river (blue points on *Figure 3*) are used a posteriori to assess the relevance of the selected models. Finally, the difference between modelled and observed mean transit time (τ_{TT} and $\tau_{TT,obs}$) is normalized by a reference age $\tau_{TT,ref}$ of 15 yr. For each catchment, the mean observed transit time ($\tau_{TT,obs}$) corresponds to the average between March and October of CFCderived ages of all springs and shallow boreholes (12 values).

Finally, the three calibration targets are combined or uncoasis of a comparable range of variations between 0 and 1, 1 being a perfect match. To this end, the normalized differences x was transformed in $e^{-x^2/2}$ (Vrugt and Sadegh, 2013). The three criteria are combined by the following minimum function to guarantee z minimum adequation for each of the target (*equation* (3)):

$$J = min\left(Nash_{lo[1]}; e^{-\frac{nRMSE^2}{2}}; e^{-\frac{1}{2}\left(\frac{|\tau_{TT,obs} - \tau_{TT}|}{\tau_{TT,ref}}\right)^2}\right)$$
(3)

The threshold J > 0.7, considered here as a good fit for the models, was chosen to select the optimal models. For such a value, the error variance of the simulated streamflow, in logarithmic scale, is limited to 30% of the variance of the observed time series. For such a value, root mean square error of the simulated nitrate concentration is smaller than 85% of the standard deviation of the observed signal (thus, smaller than 2.4, 3.8 and 2.5 mg/L for Ris, Kerharo and Douron respectively). For such a value, models with a mean transit time 12 yr higher or lower than the observed one are excluded.

Because of the strong interdependence of the four parameters (*K*, *E*, θ , τ_{NO3}), we chose to calibrate them simultaneously with a systematic sampling of the parameter space, meaning that

parameters values are sampled regularly inside a range of plausible values. The explored parameters range over broad intervals extending the typical values reported in comparable geological settings of Brittany and beyond (Table 2). Hydraulic conductivities were sampled in the range $2 10^{-7}$ - 10^{-4} m/s wider than the range of 10^{-6} - $2 10^{-5}$ m/s derived from previous regional studies in shallow aquifers of Brittany (Clément et al., 2003; Grimaldi et al., 2009; Kolbe et al., 2016; Le Borgne et al., 2006; Legchenko et al., 2004; Martin et al., 2006; Roques et al., 2014). Porosities as high as 50% have been found in shallow weathered zones (Kovacs, 1981; Wright and Burgess, 1992) while granites and schists have lower provides (0.1-1%) (Earle, 2015; Hiscock, 2009; Singhal and Gupta, 2010). Averaged over the whole weathered and fissured horizons, we considered a 1-20% range for the porosity alues. A range of 50 to 300 m for the aquifer thickness was derived from a regional synthysis for the weathered and fissured zones built based on well logs (Mougin et al., 2 $\cdot 08$, 2006). Thus, transmissivity values from 1 10^{-5} to $3 10^{-2}$ m²/s were tested. A 1–150 yr range for the characteristic denitrification time covers all possible values as values lower than 1 v. correspond to almost instantaneous denitrification. A case without denitrification was viso included. Each parameter interval was regularly discretized (in a logarithmic scale for hydraulic conductivity and denitrification time) with the number of values given by the right column of Table 2. The number of values was adapted to the width of the interval. Resulting from the parameter combinations, 19 200 simulations were run for each catchment. For each simulations the criterion *J* was computed (*equation* (3)).

Table 2: List of the calibrated parameters (left column) with the range of values explored (middle column) and the number of values explored (right column).

Parameter	Range	Number of values
Hydraulic conductivity K [m/s]	2 10 ⁻⁷ -1 10 ⁻⁴	30
Porosity θ []	0.01-0.2	16
Thickness <i>E</i> [m]	50-300	5
Denitrification time τ_{NO3} [yr]	1-150 + no det it. ≥rse (∞)	8

3.2.4 Model properties

Several properties were compute on the calibrated models to characterize their hydrological and geochemical behavior. The hydrological behavior was characterized using the characteristic hydraulic response time, he percentage of young water in the river and the relative extent of the seepage zone. The geochemical behavior was characterized using the mean transit time, the Damköhler number and the characteristic denitrification depth. We underline that we use the Damköhler number and the characteristic to compare chemical and physical processes and not as a full interpretation framework of denitrification processes like what has been proposed in riparian and hyporheic zones (Gu et al., 2007; Harvey et al., 2013; Ocampo et al., 2006a).

The hydraulic response time τ_H is the characteristic delay between a recharge event and the increase of flow in the river. It is defined by *equation* (4) (Gelhar, 1974; Molénat et al., 1999; Townley, 1995):

$$\tau_H = \frac{\theta L^2}{K E_{wet}} \tag{4}$$

where E_{wet} is the mean saturated thickness. The young water percentage is here defined as the contribution to the river of waters infiltrated during the same year. This percentage is dominantly controlled by surface processes as well as shallow groundwater transfers with short transit times if hydraulic conductivity is high. It is obtained by a particle tracking approach (Supplementary Material). The relative extent of seepage can be calculated with the surface area where overflows occur (*Figure 5*). The overall existence of seepage in Brittany during the winter season is confirmed by field observations (Franks et al., 1998; Merot et al., 2003). Seepage occurs mostly in winter because of the proximity of the water table to the surface and because of the recharge period concentrated on a restricted time range from November to March. The percentage of seepage areas should be smaller than 31% for the Gree catchments as estimated from geomorphologic and climate data (MEDDE and C'S (ol, 2014). While not a direct target of the calibration process, the existence and relative amportance of seepage will be used to confirm the consistency of the calibrated model.

The geochemical behavior of the model is characterized by the mean transit time and the Damköhler number. The mean transit time τ_{TT} is the mean travel time of an element from its inlet in the catchment to its outlet in the river defined by *equation* (3). It is straightforwardly given by the ratio of the equifer volume to the overall recharge. The Damköhler number *Da* is defined as the ratio of the characteristic denitrification time and transit time (Ocampo et al., 2006b) (*equation* (5)):

$$Da = \frac{\tau_{TT}}{\tau_{NO3}} \tag{5}$$

When the Da is smaller than one, the process is reaction limited, while when the Da is larger than one, the process is reaction limited. The denitrification time τ_{NO3} can be related to a characteristic depth of denitrification in the aquifer using the classical stratification law illustrated on *Figure 5* according to which the transit time at a position x and at a depth z is equal to (*equation* (6)):

$$\tau = \tau_{TT} \times ln\left(\frac{E(x)}{(E(x) - z)}\right) \tag{6}$$

where E(x) is the saturated thickness at x (Vogel, 1967). Assuming that E(x) can be approximated by the mean saturated thickness E_{wet} , we can combine equation (6), (5) and (1) to derive the characteristic denitrification depth z_{NO3} normalized l v the mean saturated thickness such as (*equation* (7)):

$$\frac{Z_{NO3}}{E_{wet}} = 1 - (1 - r)^{\frac{1}{D\alpha}}$$
(7)

where r is the progress of the reaction ranging between 0 and 1 respectively for a zero denitrification and a complete denitrification reachy, we will consider in this study the normalized characteristic denitrification reach at r = 25%. While it does not mean that denitrification occurs specifically at this lepth, it traduces the characteristic denitrification time in terms of characteristic depth, which could ideally be related to lithological changes (Kolbe et al., 2019).

4 Results

4.1 Catchment hydrological functioning deduced from field data

The preliminary analysis of the field data reveals the existence of rapid transfers from precipitation to river flows. Streamflow increases quickly after the dry season showing a fast response typical of the rapid saturation of lowland areas close to the river (*Figure 2*). Streamflow decreases slowly after the main recharge period occurring around the winter season, a typical

response of groundwater flow systems. Interpreted as an exponential decrease of streamflow with time, characteristic response times range between some weeks to a few months. The exponential decrease typically comes from the drainage of a reservoir where streamflow and its derivative are linearly proportional (Brutsaert and Nieber, 1977).

Chemical samplings in wells show two well marked components in groundwater (*Figure* 6). The first component made of "shallow subsurface waters" sampled mostly in shallow wells (<20m) is characterized by high nitrate concentrations (~25–50 mg/^T.) and transit times of 20 to 25 years as determined by the concentrations of CFCs. It already could from the contribution of different groundwater flowpaths (Supplementary Material). The second component made of "deep water" sampled in deeper wells (from 30 to > 10 c/a) has almost no nitrate and no CFCs revealing transit times higher than 40 years. This failer is obtained considering a gamma transit time distribution (using a shape parameter of 0.5) as the exponential distribution gives values between 60 years and hundreds of years (frection 3.1.2).

In the rivers and springs, nitrate concentrations (10–30 mg/L) are intermediate between these two components (*Figure o*, Transit times estimated from CFCs sampled in rivers establish mostly around 20 years and a clud 20 to 25 years for the springs (*Figure 6*), similar to shallow wells. The springs and all reconcentrations and transit times result from the mixing of surface water i.e. water from saturated areas and from the top of the watershed during high water levels, and of the two groundwater components identified above: shallow subsurface (shallow wells) and deep subsurface discharges (deep wells). Regarding the original data sampled in rivers, the deduced transit time should be taken as a lower bound because CFC concentrations measured in the rivers are lower than the current atmospheric concentration, thus exchanges with the atmosphere can only increase river CFC-concentrations and biased estimations towards younger

transit times. Finally, the fast surface component defined as "young water", including saturation excess overland flow and < 1yr subsurface waters, was probably weakly sampled during our campaign because this component occurs in the most superficial part in downstream areas and during punctual precipitation events.

Sontrales



Figure 6: Characteristic groundwater transit times derived from CFC concentrations with an exponential transit time distribution (or a gamma distribution for older and deeper boreholes) and nitrate concentrations from two sampling campaigns performed in March 2019 and October 2019. The two graphs on the bottom represent the average over the three catchments displayed above.

Estimated mean transit times (~20 yr) from rivers, springs and shallow wells are in line with the long-term nitrate data analysis performed by Dupas et al. (2018) who found a delay of 10 yr between the downward trend of inputs and outputs across Brittany. More recently, Dupas et al. (2020) obtained median transit times ranging from 4 to 16 yr, while Martin et al. (2006) suggested a mean groundwater residence time of 14 yr at hillslope scale.

The three end-members (surface young water, shallow subsurface and deep subsurface components) have different effects on the nitrate concentration of the receiving water bodies (springs and rivers). The two groundwater components deley the response of the river to the applied nitrate signals. In the three rivers considered, the decrease of nitrate input in the 1990-2000 period (*Figure 4*) is shifted in the river to the 2000-2010 period (*Figure 3*). As a result, river concentrations still decrease in the 2000-2010 period while nitrate input concentrations have stabilized. At smaller seasonal and inter-a. nucl scales (1-5 years), nitrate concentrations strongly vary as a result of the large variations of the surface flow component, of the nitrate inputs between seasons and between succensive years, and soil processes variations. Simple correlations are however limited because on the superposition of flow processes operating on different time scales as well as because on the superposition with complex input flow and nitrate forcing conditions.

This preliminary analysis shows the importance of the groundwater transit time stratification and of the aquifer saturation conditions on river nitrate concentrations. Transit time stratification fundamentally comes from the decrease of flow with depth (Bresciani et al., 2014; Vogel, 1967). It is often enhanced by the reduction of hydraulic conductivity with depth but does not require it. Aquifer saturation essentially controls the relative contribution of surface flows through the presence and extent of the seepage area. These two essential processes are the basis

of the hillslope model presented in section 3.2.4 and developed to further quantify the control of flow organizations on downstream nitrate concentrations.

4.2 **Properties of the calibrated models**

The calibration method described section 3.2.3 has been successively applied to the three catchments. The selection criterion J > 0.7 has been met in the three cases for 6 to 36 models of the 19 200 tested models. The objective criterion J is on average (qual to 0.73, 0.83 and 0.75 for the selected models of Ris, Kerharo and Douron catchment respectively. It goes up to 0.78, 0.91 and 0.78 respectively. The hillslope modeling approach $p_{\rm F} arcs$ to be relevant to capture the main features of the available observations on all three catchments. Even though it is parsimonious, the hillslope model has essential caracities for simulating the previously discussed dynamics and their effects on the transport of the J and $p_{\rm T}$ and reactive transport. The range of values of the calibrated parameters given in $Ta^4 le 3$ and $p_{\rm T}$ with their properties defined in section 3.2.4 shows the key features of the equivaler is rater height, hydraulic conductivity and denitrification capacity.

Parameters	Ris	Kerharo	Douron
K [m²/s]	8 10 ⁻⁶ -8 10 ⁻⁵	1.8 10 ⁻⁵ -1 10 ⁻⁴	6 10 ⁻⁶ –2.2 10 ⁻⁵
θ[]	0.025-0.1	0.03–0.12	0.025–0.05
E [m]	100-300	100240	100-300
$ au_{NO3}$ [yr]	100–∞	50-100	50–100
τ _H [yr]	0.24–0.65	0.11–0.47	0.32–0.78
Young Water [%]	7–14	6–12	12–15
Proportion of seepage zone [%]	27	1-4	3–8
$\theta E_{\text{wet}}[m]$, 4–12.3	9.2–14	5.3–7.9
<i>τ_{TT} [yr]</i>	15–25	21–32	10–15
Da []	0.12–0.17 0 if no denit.	0.32–0.55	0.15–0.2
25%-denitrification dep(.) [equivalent depth req are ¹ to achieve denitrific. ⁴ o. of .5%], expressed as a % of the total equivalent water height	82–91% (7–9m of eq. water height)	41–59% (5–6m of eq. water height)	76–85% (5–6m of eq. water height)

Table 3: Range of calibrated values for the four parameters (K, E, θ , τ_{NO3}) with the associated range of model properties defined by section 2.2.4 (grey background).

The porosity θ and hillslope thickness *E* are in the middle and upper ranges of the explored values (*Table 2*). They display significant uncertainties with factors of variations from 2 to 4 between the highest and lowest interval bounds. Both intervene in the global groundwater volume scaling with their product. The equivalent water height θE_{wet} and the mean transit time (*equation* (2)) are much better defined with uncertainties limited to a factor of variations of at most 1.7 because parameters compensate each other. The mean transit time is efficiently

constrained by the groundwater age tracing of the CFCs and by the observed long-term trend of nitrate concentration in the river (delay between the applied and discharged nitrate, mean concentration and long-term trend between 2000 and 2010).

The calibrated values of the hydraulic conductivity K (*Table 3*) are in the upper range of the explored interval (*Table 2*). Their uncertainty is higher than that of θ and E with a factor of variation between 3.5 and 10. It might however be interpreted as a limited uncertainty given that hydraulic conductivities can vary over several orders of magnitudes (nearly three orders of magnitude in the explored values). Hydraulic conductivity should be small enough to allow the occurrence of seepage and high enough to reproduce the dynamics of streamflow recession. Indeed, hillslopes should not be too conductive for the cepage area to develop in the winter season. Even if the seepage area is restricted to 1-2% on average, the percentage of young water in the river can go up to 6–15% as receiver is positively correlated with the occurrence of seepage (*Table 3*). To the opposite, hullslopes should be conductive enough to capture the relatively quick recessions of character stactimes τ_H between 0.11 yr and 0.78 yr. The relevance of the hillslope model is confirmed by its possibility to fulfill both constraints with a restricted uncertainty.

The denitrificatio. time τ_{NO3} (*Table 3*) is in the upper range of the explored interval (*Table 2*). Values mostly between 50 and 100 years show that denitrification is limited but not negligible. Only one of the qualified solutions for the Ris catchment does not require any denitrification. The occurrence of denitrification is confirmed by the values of the Damköhler number smaller than 1: 0.1-0.2 for Ris and Douron and 0.3-0.5 for Kerharo. The Damköhler number is well constrained showing that denitrification is separated from dilution by the simultaneous analysis of CFCs, which can be interpreted as reference conservative tracers. The

occurrence of denitrification is eventually confirmed by the values of the produced dinitrogen gas (N_2) measured in the samples (Supplementary Material). Indeed, the increase of N_2 appears inversely correlated to the nitrate concentration highlighting the transformation of NO_3^- into N_2 . Moreover, high sulfate concentrations are observed in deep wells associated with low nitrate concentrations (Supplementary Material) suggesting pyrite oxidation and nitrate reduction (Green et al., 2016; Korom, 1992). Associated with the natural stratification of times in the aquifer, the small Damköhler numbers indicate that denitrification occurs mostly in the lower part of the aquifer. The characteristic 25%-denitrification depth. *ranges* between 41% and 91% of the equivalent water height. Thus, only around 25% of the 4-enitrification is achieved in the first 5 to 9 meters of the equivalent water height.

While globally similar, the three catc'n ants show slight differences. The Kerharo catchment has both higher hydraulic conductivity and porosity than the two other Ris and Douron catchments. It is consistently unduced by smaller hydraulic characteristic times and higher transit times. In the same time Damköhler number indicates a more efficient denitrification. From Figure 3 and 4, one can see that both river concentration and inputs for Kerharo reduced faster from 2000 to 2010 making difficult to interpret the different properties obtained. The higher transit time in Kerharo should lead to a smoother behavior but the decrease from 2000 to 2010 is accentuated by the more efficient denitrification.

As an intermediary summary, the combination of river flows, river nitrate concentrations and CFC concentrations is relevant to model the dominant factors controlling the overall flow, conservative transport and first-order nitrate reactive transport. Catchments have well defined hydraulic parameters. Denitrification is well separated from dilution thanks to the simultaneous analysis of nitrates and CFC which provides the groundwater residence time, heterotrophic

denitrification being further quantified through sulfate and nitrogen excess measurement (Supplementary Material). The Damköhler values show the limited but non-negligible amount of denitrification mostly in the lower part of the aquifer, even though dilution in the full groundwater volume plays a more important role on the resulting nitrate concentrations. In the next section, we investigate the consequences on the extrapolation capacities of the proposed modeling approach.

4.3 Retrospective and prospective evolutions of nurate concentrations in rivers

We compare the observed and simulated nitrate concentrations in rivers obtained for the successfully calibrated models between 2000 and 2(1) (inserts on *Figure 7*). The main trends of the concentration are well reproduced for the three catchments. The inter-annual variations are also well reproduced for the Ris and E puron catchments but they are comparatively too smooth for the Kerharo catchment. The dowly are trend since 2000 for the Ris and Kerharo catchments and the stability for the Dour in patchment reflect the trends observed in the input nitrate concentrations of the ground water recharge (*Figure 4*).

The calibrated n. ocle remain very close to each other in the calibration period (2000-2010) (*Figure 7*). They slightly differ when considered over the full simulation period 1955-2015 according to the denitrification time. We recall that the calibrated denitrification and transit times are correlated. Larger denitrification times are compensated by larger aquifer volumes and so by larger transit times. In other words, the lower denitrification is compensated by a higher dilution buffering the input concentrations. It results in systematic lower peaks and slower decreases of the nitrate concentrations for the high denitrification times obtained for the purple and green lines for the Ris catchment, and for the dark blue lines for the Douron and Kerharo catchments
(inserts on *Figure 7*). More in details, the calibrated models of the Ris catchment are within the range of the 1975-1985 observed concentrations (black dots on *Figure 7*) thanks to consistent evaluations of the mean transit times with the CFCs age data (see Supplementary Material).

Observed concentrations between 2010 and 2015 for the Ris and Kerharo catchments are also overall well predicted showing the relevance of the approach in a 5-year extrapolation exercise. Note that the additional 2010-2015 data for the Ris catchment tend to exclude the models without enough denitrification. Uncertainty and equificability on the denitrification parameter and on the mean transit time would be reduced by exercising the calibration period as already stated in other studies such as Kirchner (2016a, 2015b).

35



Figure 7: Modeled nitrate concentrations (colored lines) and observed nitrate concentrations (black lines and dots) compared to the nitrate concentration in the recharge (dashed lines). Blue lines refer to the retrospective concentrations. Red and green lines stand for the prospective "business as usual" (red) and "nitrate input sudden stop" (green) scenarios. The grey areas illustrate the predictions obtained when the

threshold on the Nash-log criteria is lowered from 0.7 to 0.5. The insert for each catchment represents these calibrated models (colored lines) and the field observations (black line) focused on the calibration period. Data are presented at annual scale.

We further assess the long-term response of each catchment to two well-differentiated nitrate input scenarios from 2010-2015 to 2050 using the calibrated models. Scenarios begin in 2010 for the Douron catchment and in 2015 for the Ris and Kerharo catchments. The first scenario consists in constant nitrate inputs equal to the mean inputs of the 2010-2015 period for the Ris and Kerharo catchments, 2005-2010 for the Douron (1c1 uashed lines of Figure 7). It is called the "business as usual" scenario. The second scenario starts like the first scenario until 2025 when the input nitrate concentrations drop to 0 mg/L simulating a sudden ban of nitrate (green dashed lines of Figure 7). It is called the "intrate input sudden stop" scenario. Both scenarios do not strictly represent actual socio-economic or target scenarios but constitute synthetic experiments to characterize the catchment response times. The "business as usual" scenario is used to assess the curre in trajectory. The "nitrate input sudden stop" scenario assesses the minimum time required to teach a given river concentration after a sudden drop of inputs. During the simulation period from 2010-2015 to 2050, the typical seasonal signal of the inputs is reproduced from the mean pattern over the existing data chronicle (monthly groundwater recharge rates and associated nitrate concentrations from 1997 to 2010). Consequently, interannual variability is removed from the input scenarios while seasonal fluctuations are still reproduced.

The predicted responses of the three sets of calibrated models to the two scenarios are presented by the red and green lines on *Figure 7*. The limited variability among simulations (at most 15% the mean river concentration of the "business as usual scenario") shows that the

37

approach is relevant to predict the overall evolution of the nitrate concentrations. Moreover, lowering the acceptability threshold of the objective criterion J from 0.7 to 0.5 leads to similar results as illustrated by grey shaded areas (~100 models for each catchment) on *Figure 7*. This confirms the reliability of the approach. Variability is mainly due to the characteristic denitrification and transit times as detailed previously.

In the "business as usual" scenario, for the Douron river which inputs are relatively stable during the 1990-2010 period, an almost instantaneous quasi-stationary behavior is observed while Ris and Kerharo concentrations still gently decrease coull 2050. The gap between the nitrate inputs (dashed lines) and outputs (solid lines) h. the Douron case comes from the denitrification. In the two other cases, the evolving e^{-p} also comes from the progressive reduction of the legacy aquifer storage.

The persistence of nitrate in the aquifer is further illustrated by its reaction to the "nitrate input sudden stop" experiment as groundwater recharge is cleaned from any nitrate. The nitrate concentrations sharply drop in the rivers in the first year (6-10% for the Ris, 5-9% for the Kerharo, 11-14% for the Dourder) as the direct contribution of nitrate from the surface excess overland flow ceases. The drop is logically higher for the Douron because of its larger seepage zone. The ensuing decreare is smoother and shows the persistence of nitrate in the aquifer. Ten years after the nitrate input stop, the removal rate is 32-51% for the Ris river, 29-47% for the Kerharo river and 56-71% for the Douron river. The faster removal for the Douron comes from its smaller transit time (*Table 3*).

The retrospective analysis shows the quality of the calibration. The prospective analysis highlights the effects of the different processes on the nitrate river concentrations. The interception with the surface controls the short-term release of the nitrate. The aquifer volume

determines the mean transit time of the nitrate and, in turn, the characteristic renewal time, while the Damköhler number indicates the denitrification potential.

5 Discussion

Streamwater nitrate response is the result of past nitrate inputs convolved with catchments intrinsic geo(morpho)logical and biogeochemical properties. As developed in the three following sections, the successfully calibrated models presented in this pape. *P*llow us to further:

- 1. decompose the overall nitrate budget to characterize nitrate storage, removal and discharge;
- 2. track the nitrate location in the aquifer thanks to the spatially resolved modelling approach;
- 3. infer the role played by the relative organization of rock properties on denitrification potential, a basis for upscaling to othe, sites the characterization of nitrate legacy.

5.1 Catchment-scale nitrate storage and legacy

We determined the long-torm catchment scale nitrate storage by an integrated budget of the nitrate entering, leaving and coing degraded within the aquifer based on the calibrated models. The nitrate fluxes and budget are extracted from the model over the full 1955-2010 period for the three studied catchments. Results are presented as the overall quantity of nitrate discharged to the river, stored in the aquifer and removed by denitrification. All three terms are normalized by the integrated inlet quantity of nitrate over the same period (*Table 4*). We discuss successively the three terms: nitrate still stored in the aquifer, discharged to the river, and degraded in the aquifer.

Table 4: Nitrate mass denitrified in the aquifer, discharged to the river and stored in the aquifer integrated over the 1955-2010 period and normalized by the integrated inlet quantity of nitrate derived

from the successfully calibrated models on the three studied catchments. The mass balance is presented for three specific models: the value in bold characters refers to the model which denitrification rate is the median (Med) of the distribution obtained from the calibrated models. The other two sub-columns indicate the results obtained for models having the minimum (Min) and maximum (Max) denitrification rates. Note that, while the median value of denitrification (Med) is necessarily between the minimum and maximum, it does not have to be the case for river discharge and aquifer storage as min and max do not refer to these parameters.

Nitrate budget over 1955-2010	Ris			Kerharo			Douron		
	Min	Med	Max	Min	Mad	Max	Min	Med	Max
Denitrification %	0	9	11	13	21	22	10	14	14
River discharge %	61	60	64	1.)	54	51	65	70	69
Aquifer storage %	39	31	25	38	25	27	25	16	17
Median case Denitrified Stored				13 21			19 14 16		
 Discharged Discharged young fraction 	Mean vater tra vsit time : 21 yr			Mean water transit time : 23 yr			51 Mean water transit time : 10 yr		

The first term is the nitrate still stored in the aquifer, obtained by integrating the concentration of all model's cells in 2010. It is determined more by the river discharge than by the denitrification as the river discharge is 3 to 6 times larger than the denitrification. The proportion of stored nitrate is larger for the Kerharo (27-38%), intermediate for the Ris (25-39%) and smaller for the Douron (17-25%) consistently with the quantity of water stored (θE_{wet}) increasing by a factor of around two from the Douron to the Kerharo (*Table 3*).

The second term is the nitrate discharged to the river computed from simulated streamflow and river concentration. It comes both from nitrate leaving the aquifer over the period and from nitrate that were inlet on saturated surfaces, did not enter the aquifer and flew directly to the river. The nitrate discharge rate was largest for the Douron (65-70%) and smallest for the Kerharo (49-54%). It is quite high, representing around two thirds of the total input to the aquifer. Uncertainties on discharged masses from 1955 to 2010 are limited thanks to the constrain provided by observed streamflows and river concentrations from 2000 to 2010. Note that nitrate discharged through the river after less than one ver of transit time contributed only slightly to the output (10-21%) (*Table 4*) like water flows (15%) (*Table 3*). At regional to global scales, young water proportion might generally be la er as suggested by the analysis of Jasechko et al. (2016), who found a median value of 21% and a 10th - 90th percentile range of 4–53% on 254 watersheds around the world legarding the average contribution of river waters younger than three months. Comparing h issing nitrogen (input minus river export) in the aquifer relatively to the quantity discharged in the river, we found a ratio of 0.4-1 while a value of 0.3-2.4 was estimated by Dupas et a. (2020) and 0.7 by Aquilina et al. (2012), both at Brittany scale. Typical retention rates including soil and aquifers ranges from 80 to 90% of total nitrogen input (Aquilina et al., 2012; En. hardt et al., 2019; Lassaletta et al., 2012).

The third term comes from the rates of denitrification and is deduced from the nitrate budget. They are comparable across the three different catchments. They amount to non-negligible 9-21% median values even though the denitrification rate is relatively low as shown by the small Damköhler number and high characteristic denitrification times of *Table 3* although the estimated denitrification in the aquifer could be slightly overestimated as it integrates potential but limited heterotrophic in-stream denitrification. For the Douron and Kerharo,

denitrification rates reach 10-14% and 13-22% respectively. The Ris presents smaller denitrification rates, which might reflect less capacity for this granitic catchment to remove past accumulated nitrate. While the higher denitrified mass for the Kerharo comes with a longer mean transit time compared to Ris and Douron, the optimal (regarding criterion I) denitrified mass inside one catchment appears to be not correlated to its optimal mean transit time. Indeed, despite quite similar transit times for Ris and Kerharo (21-23 yr), denitrified mass is respectively 9 % and 21 % while the smaller transit time for the Douron (10 vr) coincides with a 14 % denitrified mass. The comparison between the three catchments highlights that the denitrification potential is not only governed by the mean transit time bu, also by other factors. Denitrification cannot be interpreted as a uniform process within the it aquifer volume like what might be done within a simplifying Damköhler framework, see ording to which any increase of the transit time would be traduced by additional der trification. As developed below, denitrification additionally depends on the depth of the reduced zone. Above, denitrification would not occur whatever the transit time, while, below Jenitrification would occur almost whatever the transit time. In such conditions, the Demkohler number characterizes the stratification of the reduced zone rather than the reaction time per se. While relevant in other hydrological compartments like the hyporheic and riparia. zones, it might not be relevant to aquifers as previously hinted (Kolbe et al., 2019; Pinay et al., 2015). We further discuss this conclusion in the next sections by quantifying the impact of the nitrate concentrations stratification and by defining an aquifer denitrification potential.

5.2 Stratification of the nitrate storage and denitrification potential

Beyond the overall nitrate budget, the calibrated models can further be used to assess the spatial distribution of the nitrate concentrations and especially their stratification within the

aquifer. Figure 8a shows the evolution of the nitrate concentration with depth of the water height at the middle of the hillslope (x=L/2) for 3 000 models applied to the Ris catchment and selected randomly from the parameter space (for computational reason). The successfully calibrated models (materialized in orange and yellow) display very close nitrate stratification. The nitrate stratification pattern appears to be well constrained by the calibration data while it was not in the calibration target *I* (on *Figure 8a*, models with high *I* value display similar stratification). This result is obtained freely from the vertically resolved approach. We underline that stratification appears naturally through the increase of the transit time with depth and agrees with the typical nitrate profiles found in similar hydrogeological reservoir. (Faillat et al., 1999; Molenat et al., 2008; Molénat et al., 2002). It does not require any decrea e of hydraulic conductivity with depth but a decrease of hydraulic conductivity world enhance the stratification. Lithological stratification is often assumed in other models of shallow Britain aquifers based on field evidences like in the soil and groundwate" hillslope-scale two-linear reservoirs model of Fovet et al. (2015) or in the spatialized model of stratified hydraulic conductivity at catchment scale (Kolbe et al., 2016) and hillslope scale (Martin et al., 2006).



Figure 8: Aquifer stratification of nitrate concentrations for the Pis catchment. Nitrate concentrations at the middle of the catchment (x=L/2) (horizontal axis) are presented against the equivalent water thickness taken as the product of the porosity by the and the order table (vertical axis) (a) for 3 000 models in 2005 with different model to data a equivalent represented by the calibration criterion J and (b) for one of the best models as a function of the profile is added in red on (b). The mean groundwater transit in a profile is added in red on (b). The best model represented on (b) is obtained for an aquifer the kness of 150 m, a porosity of 5%, an hydraulic conductivity of $1.8 \times 10-5$ m/s and a denitrification time of 100 yr. The dashed lines on (b) represent the simulated nitrate concentration in 1995 and 1010 when no denitrification is considered.

The nitrate vertical distribution is far from uniform, it is stratified. It globally echoes the input nitrate concentration shown in *Figure 4* in a deformed way as the groundwater transit time increases non-linearly with depth (*Figure 8b*, red line) and because denitrification increases with depth (*Figure 8b*, blue to green lines). The concentration peak is reached in 2005 at 5-6 meters corresponding to the peak of input concentrations of 1990 consistently obtained for a transit time of around 15 years. *Figure 8b* shows the vertical progression of the nitrate concentrations from 1970 to 2010 and the peak appearance in 1995 around two meters and deepening with time. The

decrease of the peak due to the denitrification is limited to around 20% in 15 years. The denitrification is much more effective deeper when the transit time sharply increases (*Figure 8b*, red line). Nitrate becomes fully degraded at the bottom of the aquifer model where the no-flow boundary condition slows down the transported elements long enough for the nitrate to be degraded. The limited amount of denitrification in most of the aquifer comes from the high characteristic depth at which 25% of the input nitrate are degraded intervening at 82-91% of the full equivalent water height of the aquifer (*Table 3*). It is also use case for the Douron and Kerharo with somewhat smaller but still high depths. In the unce studied cases, most of the denitrification only occurs close to the basis of the modelled aquifer. We further discuss this important point in the next section.

5.3 Emergence of denitrification as a lithological interface process

Knowing where denitrification processes occur within aquifers and the drivers of this localization is crucial to predict denitrification efficiency. In the literature, two main features of aquifers have been previously pointed out for their role on denitrification efficiency: the volume -through residence time- and we existence of a geochemical interface (Kolbe et al., 2019; Liao et al., 2012; Tesoriero et al., 2005; Van Der Velde et al., 2010b; Van Meter and Basu, 2015). Based on the present results, these hypotheses are further questioned and we propose a new hypothesis based on a hydrodynamic interface to explain the denitrification processes within aquifers.

First, it is commonly accepted that the greater the volume, the greater the residence time and the greater the denitrification. However, here no correlations were detected between mean transit time and total denitrified mass when comparing the calibrated models. Indeed, the denitrified percentage on the Kerharo catchment is twice higher than on the Ris while they have

close mean transit times and the denitrified percentage on the Douron is higher than on the Ris while the mean transit time on the Douron is twice smaller (*Table 4*). In some cases, the percentage of denitrification could thus increase with a decreasing aquifer volume. We hypothesize that it is due to the flow decrease with depth, in other words, a shallower base of the aquifer would favor a higher overall denitrification rate. This assumption brings new insights into the control on denitrification of groundwater flow structure but should be further tested on different sites and at larger scales.

Second, recent studies highlighted the vertical stratification of denitrification reactivity because of geochemical interfaces in aquifers (Green et al., 2010; Kolbe et al., 2019). Autotrophic denitrification in crystalline basements is indeed closely linked to geology and weathering processes and thus highly related to reochemical interfaces. It occurs when oxygen levels are low enough for nitrates to become competitive electron acceptors and when reduced mineral are available as electron (o.prs. Autotrophic denitrification has been commonly associated to sulfur minerals such as pyrite (Böhlke et al., 2002; Pinay et al., 2015) or iron-rich reduced minerals such as biotite (Aquilina et al., 2018). In this framework, denitrification is often considered null in the weath red layer because of prevalent oxic conditions and of weathered reduced minerals. The continuous water flows from the surface bring oxygen and nitrate progressively passivating down mineral surfaces through oxide precipitation, thus slowing down and limiting the denitrification reaction. This interpretation is also supported by experimental studies that have shown that a medium in which no apparent denitrification occurs can provide support for denitrification by reactivating fresh surfaces during rock grinding or during pumping at the field-scale (Roques et al., 2018b; Tarits et al., 2006).

This general framework of denitrification stratification is consistent with the results found in the present study, although we further suggest that a hydrodynamic interface might be a key driver in this stratification. Based on three study sites and successfully calibrated models of nitrate concentrations in both shallow and deep groundwater and river trends, we confirm that nitrate removal in shallow flow paths is very limited, while denitrification occurs deeper. The removal of nitrate is thus slow and does not prevent the build-up of a nitrogen legacy as previously suggested by Kolbe et al. (2019) on another aquifer in Brittany and complementary sites in California. The nitrate stratification is well simulated thanks to the simulated stratification of groundwater flows, showing that the circu, tion pattern exerts a large control on denitrification. The key point is that the calibrated depth of denitrification (or 25%denitrification depth, see *Table 3*) is close to the base of the aquifer represented by the lowermost model limit. Similar results would be provided if permeability contrasts or denitrification timelag were accounted for. Therefore, for the first time, we show here that denitrification processes are occurring deep in the aquifer, drive, by the location of the lower boundary of the aquifer and thus by a hydrodynamic interface, which is also supported by the decorrelation between denitrification and mean transit time.

The role of a hydrodynamic interface on denitrification is not inconsistent with previous interpretations of a geochemical interface role and more data would be required to infer roles of both hydrodynamic and geochemical interfaces. This study together with previous studies nevertheless support the idea of co-evolution (Harman and Troch, 2014; Troch et al., 2013; Yoshida and Troch, 2016) where geochemical and hydrogeological properties are related. Denitrification is tightly related to the geochemical reaction along the flow-path but also to the reactive flow history of the aquifer. Geochemical reactions also alter rock properties and

47

particularly porosity and permeability, as such hydrodynamic and geochemical interfaces are likely to coincide. Under natural flows, the basement of the aquifer would provide conductive pathways but not too much developed to keep active electron donor sites. Therefore, lithology interfaces, with their hydrodynamic and geochemical aspects, likely play a central role in subsurface denitrification. Rather than an "all or nothing" interpretation, effectively slow and limited but nonetheless active denitrification processes deep in aquifers should be considered in nitrogen cycles and depollution studies.

6 Conclusion: Implications for managers

This study brings insights about our pre lie we capacity regarding water streamflow and water quality in rivers. A simple physicall, b sed groundwater model was used and informed by streamflow and nitrate concentration. measured in rivers. Additionally, independent measurements of anthropic $atmos_{p}$ beils tracers were made on boreholes, wells and rivers to derive transit times. The results on three different catchments also bring knowledge about typical catchment response times and the control of groundwater on river flows and nitrate concentrations. This study indicates that a significant part (5-15%) of the groundwater recharge reach rapidly the river (< 1 yr) through the development of seepage areas and rapid flow in the variably saturated zone. We found that mean transit time in groundwater are around decades (10–32 yr). Regarding catchments capacity to remove nitrogen excess, an important result is that denitrification appears limited to the lower part of the aquifer where flows are more limited and transit times are longer. Eventually, the overall denitrification in the aquifer only reaches 10-20 %. Consequently, an important part of nitrate is still stored as nitrate legacy in groundwater

systems (*Table 4*). While the parsimonious model developed in this study fulfills its objective, we note that running the simulation until 2020 should reduce uncertainty. A deeper understanding of processes, focusing less on groundwater, should require to include a dynamic coupling between TNT2 and the hillslope-scale aquifer model, and a potential in-stream denitrification. However, it will strongly increase the model complexity and should require to use seasonal nitrate variations in river and additional observed data.

From a management perspective, this study contributes to answer the following key question: "How much time does slow groundwater transfer dolay the effects of improved agricultural practices?". The nitrate concentration in the new results from a combination of fast and slow transfers. Slow transfers (part of subsurface and 'dep subsurface waters) result from the aquifer storage capacity assessed above. Without any further input of nitrate, the river concentration would decrease by two thir wir. 10 years for the Douron and by one third for the Kerharo, showing an important resilience of these catchments, capable of rapidly diminishing the legacy stored nitrate if no further inputs are constantly being added. The existence of rapid transfers (~1 yr) represents a heajor clue to farmers and managers. It indicates that the nitrate concentration in the river msult: from the past practices but also from the current practices (and potentially efforts of farmers). A sudden drop of nitrate inputs would lead to 5 to 25% and 15 to 50% decrease in the nitrate concentrations in rivers within 1 to 5 yr for the Kerharo and the Douron, respectively.

This study provides a precise quantitative timing of the effects of potential environmental management frameworks. It shows that the future of pollution, although partly related to past farming practices, is also the responsibility of present practices and environmental measures.

49

Acknowledgments

This study was funded by the "Région Bretagne" authorities, the "DREAL" Department (Ministery of Environment) and the Water Agency "Agence de l'Eau Loire-Bretagne" through the MORAQUI (MOdélisation de la Réactivité des AQUIfères dans les bassins algues vertes) project. We thank the Public offices "EPA Baie de Douarnenez" and the "Communauté de Communes de Morlaix", and the Water Regional Technical Center " CRESEB" for data collection and field work as well as the "Condate-Eau" (CSU-Jniv. Rennes 1) analytical platform for the chemical and dissolved gases analysis.

Bibliography

- Abbott, B.W., Moatar, F., Gauthier, O., Foret, O., Antoine, V., Ragueneau, O., 2018. Trends and seasonality of river nutrients in agricultural catchments: 18 years of weekly citizen science in France. Sci. Total Environ. 524, 845–858. https://doi.org/10.1016/j.scitotenv.2017.12.176
- Aquilina, L., Roques, C., Boi son, A., Vergnaud-Ayraud, V., Labasque, T., Pauwels, H., Pételet-Giraud, E., Pettenat, M., Dufresne, A., Bethencourt, L., Bour, O., 2018. Autotrophic denitrification supported by biotite dissolution in crystalline aquifers (1): New insights from short-term batch experiments. Sci. Total Environ. 619–620, 842–853. https://doi.org/10.1016/j.scitotenv.2017.11.079
- Aquilina, L., Vergnaud-Ayraud, V., Labasque, T., Bour, O., Molénat, J., Ruiz, L., de Montety,V., De Ridder, J., Roques, C., Longuevergne, L., 2012. Nitrate dynamics in agricultural catchments deduced from groundwater dating and long-term nitrate monitoring in surface-

and groundwaters. Sci. Total Environ. 435–436, 167–178. https://doi.org/10.1016/j.scitotenv.2012.06.028

- Ayraud, V., Aquilina, L., Labasque, T., Pauwels, H., Molenat, J., Pierson-Wickmann, A.C., Durand, V., Bour, O., Tarits, C., Le Corre, P., Fourre, E., Merot, P., Davy, P., 2008.
 Compartmentalization of physical and chemical properties in hard-rock aquifers deduced from chemical and groundwater age analyses. Appl. Geochemistry 23, 2686–2707. https://doi.org/10.1016/j.apgeochem.2008.06.001
- Bakker, M., Post, V., Langevin, C.D., Hughes, J.D., White, J.T. Ctarn, J.J., Fienen, M.N., 2016. Scripting MODFLOW Model Development Using Python and FloPy. Groundwater 54, 733–739. https://doi.org/10.1111/gwat.12413
- Beaujouan, V., Durand, P., Ruiz, L., 2001. Moanding the effect of the spatial distribution of agricultural practices on nitrogen fluxes in rural catchments. Ecol. Modell. https://doi.org/10.1016/S0304-3800(00)00435-X
- Beaujouan, V., Durand, P., Ruiz, J. A mousseau, P., Cotteret, G., 2002. A hydrological model dedicated to topography-ba. ed simulation of nitrogen transfer and transformation: Rationale and application to the geomorphology-denitrification relationship. Hydrol. Process. 16, 493–507. https://doi.org/10.1002/hyp.327
- Bedekar, V., Morway, E., Langevin, C., Tonkin, M., 2016. MT3D-USGS version 1: A U.S. Geological Survey release of MT3DMS updated with new and expanded transport capabilities for use with MODFLOW. Groundw. Resour. Progr. 84. https://doi.org/10.3133/tm6A53
- Benettin, P., Bailey, S.W., Rinaldo, A., Likens, G.E., McGuire, K.J., Botter, G., 2017. Young runoff fractions control streamwater age and solute concentration dynamics. Hydrol.

Process. https://doi.org/10.1002/hyp.11243

- Berghuijs, W.R., Kirchner, J.W., 2017. The relationship between contrasting ages of groundwater and streamflow. Geophys. Res. Lett. 44, 8925–8935. https://doi.org/10.1002/2017GL074962
- Boers, P.C.M., 1996. Nutrient emissions from agriculture in the Netherlands, causes and remedies. Water Sci. Technol. 33, 183–189. https://doi.org/https://doi.org/10.1016/0273-1223(96)00229-6
- Böhlke, J.K., Wanty, R., Tuttle, M., Delin, G., Landon, M., 2002. Denitrification in the recharge area and discharge area of a transient agricultural must plume in a glacial outwash sand aquifer, Minnesota. Water Resourt. Res. 38, 10-1-10–26. https://doi.org/10.1029/2001wr000663
- Boulton, A.J., Findlay, S., Marmonier, P. Stanley, E.H., Maurice Valett, H., 1998. The functional significance of the hyporbeic zone in streams and rivers. Annu. Rev. Ecol. Syst. 29. https://doi.org/10.1146/annure/ccolsys.29.1.59
- Breemen, N. Van, Boyer, E.W. Faustian, K., Seitzinger, S., 2002. The Nitrogen Cycle at Regional to Global Scales. Nitrogen Cycle Reg. to Glob. Scales. https://doi.org/10.1077/978-94-017-3405-9
- Bresciani, E., Davy, P., de Dreuzy, J.-R., 2014. Is the Dupuit assumption suitable for predicting the groundwater seepage area in hillslopes? Water Resour. Res. 50, 2394–2406. https://doi.org/10.1002/2013WR014284
- Brutsaert, W., 1994. The unit response of groundwater outflow from a hillslope. Water Resour. Res. 30, 2759–2763.

Brutsaert, W., Nieber, J.L., 1977. Regionalized drought flow hydrographs from a mature

glaciated plateau. Water Resour. Res. 13, 637–643. https://doi.org/10.1029/WR013i003p00637

- Chen, D., Shen, H., Hu, M., Wang, J., Zhang, Y., Dahlgren, R.A., 2018. Legacy Nutrient Dynamics at the Watershed Scale: Principles, Modeling, and Implications, 1st ed, Advances in Agronomy. Elsevier Inc. https://doi.org/10.1016/bs.agron.2018.01.005
- Clément, J.C., Holmes, R.M., Peterson, B.J., Pinay, G., 2003. Isotopic investigation of denitrification in a riparian ecosystem in western France. J. Appl. Ecol. 40, 1035–1048. https://doi.org/10.1111/j.1365-2664.2003.00854.x
- Conan, C., Bouraoui, F., Turpin, N., de Marsily, G., Biacelio, G., 2003. Modeling Flow and Nitrate Fate at Catchment Scale in Brittany (France). J. Environ. Qual. 32, 2026–2032. https://doi.org/10.2134/jeq2003.2026
- Cornaton, F., Perrochet, P., 2007. Groundwater age, life expectancy and transit time distributions in advective dispersive systems : 1. Generalized reservoir theory 29, 1267–1291. https://doi.org/10.1016/i.advwatres.2005.10.009
- Danckwerts, P. V., 1953. Continuous flow systems. Distribution of residence times. Chem. Eng. Sci. 2, 1–13. https://dci.org/10.1016/0009-2509(53)80001-1
- Deschamps, L., Frétière, K., Maillocchon, A., Molina, V., 2016. La Bretagne: première région française pour la production et la transformation de viande, INSEE.
- Dupas, R., Ehrhardt, S., Musolff, A., Fovet, O., Durand, P., 2020. Long-term nitrogen retention and transit time distribution in agricultural catchments in western France. Environ. Res. Lett. 15. https://doi.org/10.1088/1748-9326/abbe47
- Dupas, R., Minaudo, C., Gruau, G., Ruiz, L., Gascuel-Odoux, C., 2018. Multidecadal Trajectory of Riverine Nitrogen and Phosphorus Dynamics in Rural Catchments. Water Resour. Res.

https://doi.org/10.1029/2018WR022905

- Durand, P., Breuer, L., Johnes, P.J., Billen, G., Butturini, A., Pinay, G., van Grinsven, H., Garnier, J., Rivett, M., Reay, D.S., Curtis, C., Siemens, J., Maberly, S., Kaste, Ø., Humborg, C., Loeb, R., de Klein, J., Hejzlar, J., Skoulikidis, N., Kortelainen, P., Lepistö, A., Wright, R., 2011. Nitrogen processes in aquatic ecosystems. Eur. Nitrogen Assess. 126–146. https://doi.org/10.1017/cbo9780511976988.010
- Earle, S., 2015. Physical geology, BC Open Textbooks. https://cbi.org/10.1016/B978-0-444-42758-8.50008-8
- Ehrhardt, S., Kumar, R., Fleckenstein, J.H., Attinger, S., Musolff, A., 2019. Trajectories of nitrate input and output in three nested catchments along a land use gradient. Hydrol. Earth Syst. Sci. 23, 3503–3524. https://doi.org/10.51/14/ness-23-3503-2019
- European Comission, 1991. Fighting wate. po'iution from agricultural nitrates. 91/676/EEC.
- Faillat, J.-P., Somlette, L., Sicard, T., 1>29. Controles redox et hydrodynamiques des nitrates et zonation hydrochimique vertica des nappes de fissures du socle. Possibilité de généralisation. Bull. la Soci^{*}té géologique Fr. 170.
- Fan, Y., Clark, M., Lawronce, D.M., Swenson, S., Band, L.E., Brantley, S.L., Brooks, P.D., Dietrich, W.E., Floxs, A., Grant, G., Kirchner, J.W., Mackay, D.S., McDonnell, J.J., Milly, P.C.D., Sullivan, P.L., Tague, C., Ajami, H., Chaney, N., Hartmann, A., Hazenberg, P., McNamara, J., Pelletier, J., Perket, J., Rouholahnejad-Freund, E., Wagener, T., Zeng, X., Beighley, E., Buzan, J., Huang, M., Livneh, B., Mohanty, B.P., Nijssen, B., Safeeq, M., Shen, C., van Verseveld, W., Volk, J., Yamazaki, D., 2019. Hillslope Hydrology in Global Change Research and Earth System Modeling. Water Resour. Res. 1737–1772. https://doi.org/10.1029/2018WR023903

- Fovet, O., Ruiz, L., Faucheux, M., Molénat, J., Sekhar, M., Vertès, F., Aquilina, L., Gascuel-Odoux, C., Durand, P., 2015. Using long time series of agricultural-derived nitrates for estimating catchment transit times. J. Hydrol. 522, 603–617. https://doi.org/10.1016/j.jhydrol.2015.01.030
- Franks, S.W., Gineste, P., Beven, K.J., Merot, P., 1998. On constraining the predictions of a distributed model: The incorporation of fuzzy estimates of saturated areas into the calibration process. Water Resour. Res. 34, 787–797. https://doi.org/10.1029/97WR03041
- Gabriel, D., Roschewitz, I., Tscharntke, T., Thies, C., 2006 Beth diversity at different spatial scales: Plant communities in organic and conventional agriculture. Ecol. Appl. 16. https://doi.org/10.1890/1051-0761(2006)016[2011:LTADSS]2.0.CO;2
- Galloway, J.N., Townsend, A.R., Erisman, J.W., Pek'.nda, M., Cai, Z., Freney, J.R., Martinelli, L.A., Seitzinger, S.P., Sutton, M.A., 20 J8. Transformation of the nitrogen cycle: Recent trends, questions, and potential solutions. Science (80-.). https://doi.org/10.1126/science 11.'6574
- Gambino, M., 2014. Les mutations des systèmes productifs français : le modèle breton, à revisiter. Fr. les Mutations des systèmes Prod. 371–382.
- Gburek, W.J., Folmar, G.J., 1999. Patterns of contaminant transport in a layered fractured aquifer. J. Contam. Hydrol. 37, 87–109. https://doi.org/10.1016/S0169-7722(98)00158-2
- Gelhar, L.W., 1974. Stochastic analysis of phreatic aquifers. Water Resour. Res. 10, 539–545. https://doi.org/10.1029/WR010i003p00539
- Gleeson, T., Befus, K.M., Jasechko, S., Luijendijk, E., Cardenas, M.B., 2016. The global volume and distribution of modern groundwater. Nat. Geosci. 9, 161–164. https://doi.org/10.1038/ngeo2590

- Goderniaux, P., Davy, P., Bresciani, E., De Dreuzy, J.R., Le Borgne, T., 2013. Partitioning a regional groundwater flow system into shallow local and deep regional flow compartments.
 Water Resour. Res. 49, 2274–2286. https://doi.org/10.1002/wrcr.20186
- Green, C.T., Böhlke, J.K., Bekins, B.A., Phillips, S.P., 2010. Mixing effects on apparent reaction rates and isotope fractionation during denitrification in a heterogeneous aquifer. Water Resour. Res. 46. https://doi.org/10.1029/2009WR008903
- Green, C.T., Jurgens, B.C., Zhang, Y., Starn, J.J., Singleton, M.J., Esser, B.K., 2016. Regional oxygen reduction and denitrification rates in groundwater from multi-model residence time distributions, San Joaquin Valley, USA. J. Hydrol. 543, 155–166. https://doi.org/10.1016/j.jhydrol.2016.05.018
- Grimaldi, C., Thomas, Z., Fossey, M., Fauvel, Y., '*Ae* ot, P., 2009. High chloride concentrations in the soil and groundwater under an cak hedge in the West of France: an indicator of evapotranspiration and water movement. Hydrol. Process. 23, 1865–1873. https://doi.org/10.1002/hyp.73¹6
- Gu, C., Hornberger, G.M., Mills, A.L., Herman, J.S., Flewelling, S.A., 2007. Nitrate reduction in streambed sediments. Fliccos of flow and biogeochemical kinetics. Water Resour. Res. 43, 1–10. https://doi.org/10.1029/2007WR006027
- Gupta, H. V., Kling, H., Yilmaz, K.K., Martinez, G.F., 2009. Decomposition of the mean squared error and NSE performance criteria: Implications for improving hydrological modelling. J. Hydrol. 377, 80–91. https://doi.org/10.1016/j.jhydrol.2009.08.003
- Habets, F., Boone, A., Champeaux, J.L., Etchevers, P., Franchistéguy, L., Leblois, E., Ledoux,E., Le Moigne, P., Martin, E., Morel, S., Noilhan, J., Seguí, P.Q., Rousset-Regimbeau, F.,Viennot, P., 2008. The SAFRAN-ISBA-MODCOU hydrometeorological model applied

over France. J. Geophys. Res. Atmos. 113, 1-18. https://doi.org/10.1029/2007JD008548

- Haitjema, H.M., 1995. On the residence time distribution in idealized groundwatersheds. J. Hydrol. 172, 127–146. https://doi.org/10.1016/0022-1694(95)02732-5
- Hamilton, S.K., 2012. Biogeochemical time lags may delay responses of streams to ecological restoration. Freshw. Biol. 57, 43–57. https://doi.org/10.1111/j.1365-2427.2011.02685.x
- Harbaugh, A.W., 2005. MODFLOW 2005, The U. S. Geological Survey Modular GroundWater Model: the GroundWater Flow Process. U.S. Geol. Surv. Tech. Methods 253.
- Harman, C., Troch, P.A., 2014. What makes Darwinian hyperclogy "darwinian"? Asking a different kind of question about landscapes. Hyperclogy. Earth Syst. Sci. 18, 417–433. https://doi.org/10.5194/hess-18-417-2014
- Harvey, J.W., Böhlke, J.K., Voytek, M.A., Sout, D., Tobias, C.R., 2013. Hyporheic zone denitrification: Controls on effective reading depth and contribution to whole-stream mass balance. Water Resour. Res. 49, 62>8–6316. https://doi.org/10.1002/wrcr.20492
- Hiscock, K., 2009. Hydrogeology. Principles and Practice., John Wiley & Sons. https://doi.org/10.1007/s12.65-016-5360-8
- Hrachowitz, M., Benettin, P. van Breukelen, B.M., Fovet, O., Howden, N.J.K., Ruiz, L., van der Velde, Y., Wade, A.¹., 2016. Transit times-the link between hydrology and water quality at the catchment scale. Wiley Interdiscip. Rev. Water 3, 629–657. https://doi.org/10.1002/wat2.1155
- Hrachowitz, M., Fovet, O., Ruiz, L., Savenije, H.H.G., 2015. Transit time distributions, legacy contamination and variability in biogeochemical 1/fα scaling: how are hydrological response dynamics linked to water quality at the catchment scale? Hydrol. Process. 29, 5241–5256. https://doi.org/10.1002/hyp.10546

- Jasechko, S., Kirchner, J.W., Welker, J.M., McDonnell, J.J., 2016. Substantial proportion of global streamflow less than three months old. Nat. Geosci. 9, 126–129. https://doi.org/10.1038/ngeo2636
- Jimenez-Martinez, J., Longuevergne, L., Le Borgne, T., Davy, P., Russian, A., Bour, O., 2013. Temporal and spatial scaling of hydraulic response to recharge in fractured aquifers: Insights from a frequency domain analysis. Water Resour. Res. 49, 3007–3023. https://doi.org/10.1002/wrcr.20260
- Jurgens, B.C., Bohlke, J.K., Eberts, S.M., 2012. An Excel(R) workbook for interpreting groundwater age distributions from environmental cacer data. U.S. Geol. Surv. Tech. Methods Rep. 4-F3 60.
- Kaandorp, V.P., de Louw, P.G.B., van der Velde, V., Broers, H.P., 2018. Transient Groundwater Travel Time Distributions and Ag. Renked Storage-Discharge Relationships of Three Lowland Catchments. Wheter Resour. Res. 54, 4519–4536. https://doi.org/10.1029/2017WP0.'2+61
- Kirchner, J.W., 2016a. Aggreg, tion in environmental systems-Part 1: Seasonal tracer cycles quantify young water tractions, but not mean transit times, in spatially heterogeneous catchments. Hydrol. Earth Syst. Sci. 20, 279–297. https://doi.org/10.5194/hess-20-279-2016
- Kirchner, J.W., 2016b. Aggregation in environmental systems-Part 2: Catchment mean transit times and young water fractions under hydrologic nonstationarity. Hydrol. Earth Syst. Sci. 20, 299–328. https://doi.org/10.5194/hess-20-299-2016
- Kirchner, J.W., Feng, X., Neal, C., 2000. Fractal stream chemistry and its implications for contaminant transport in catchments. Nature 403, 524–527. https://doi.org/10.1038/35000537

- Knowles, R., 1982. Denitrification. Microbiol. Rev. 46, 866–871. https://doi.org/10.1016/B978-008045405-4.00264-0
- Kolbe, T., 2017. Temporal and spatial structures of denitrification in crystalline aquifers.
- Kolbe, T., de Dreuzy, J.-R., Abbott, B.W., Aquilina, L., Babey, T., Green, C.T., Fleckenstein, J.H., Labasque, T., Laverman, A.M., Marçais, J., Peiffer, S., Thomas, Z., Pinay, G., 2019.
 Stratification of reactivity determines nitrate removal in groundwater. Proc. Natl. Acad. Sci. 116, 2494–2499. https://doi.org/10.1073/pnas.1816892116
- Kolbe, T., Marçais, J., Thomas, Z., Abbott, B.W., de Drove, J.R., Rousseau-Gueutin, P., Aquilina, L., Labasque, T., Pinay, G., 2016. Coupling 3D groundwater modeling with CFCbased age dating to classify local groundwater cl. ulation in an unconfined crystalline aquifer. J. Hydrol. 543, 31–46. https://doi.org/10.1016/j.jhydrol.2016.05.020
- Korom, S.F., 1992. Natural denitrification in the saturated zone: A review. Water Resour. Res. https://doi.org/10.1029/92WR00252
- Kovacs, G., 1981. Seepage hydraulies. Elsevier. https://doi.org/10.1016/0022-1694(84)90254-3
- Kronvang, B., Andersen, H.E., Pørgesen, C., Dalgaard, T., Larsen, S.E., Bøgestrand, J., Blicher-Mathiasen, G., 2008 Effects of policy measures implemented in Denmark on nitrogen pollution of the aquatic environment. Environ. Sci. Policy. https://doi.org/10.1016/j.envsci.2007.10.007
- Kronvang, B., Jeppesen, E., Conley, D.J., Søndergaard, M., Larsen, S.E., Ovesen, N.B., Carstensen, J., 2005. Nutrient pressures and ecological responses to nutrient loading reductions in Danish streams, lakes and coastal waters. J. Hydrol. 304, 274–288. https://doi.org/https://doi.org/10.1016/j.jhydrol.2004.07.035

Lague, D., Davy, P., Crave, A., 2000. Estimating Uplift Rate and Erodibility from the Area-

Slope Relationship : Examples from Britanny (France) and Numerical Modelling. Phys. Chem. Earth Part A Solid Earth Geod. 25, 543–548. https://doi.org/10.1016/S1464-1895(00)00083-1

- Lassaletta, L., Romero, E., Billen, G., Garnier, J., García-Gómez, H., Rovira, J. V., 2012. Spatialized N budgets in a large agricultural Mediterranean watershed: High loading and low transfer. Biogeosciences 9, 57–70. https://doi.org/10.5194/bg-9-57-2012
- Le Borgne, T., Bour, O., Paillet, F.L., Caudal, J.P., 2006. Assessment of preferential flow path connectivity and hydraulic properties at single-borehole and cross-borehole scales in a fractured aquifer. J. Hydrol. 328, 347–359. https://doi.org/10.1016/j.jhydrol.2005.12.029

Le Moigne, P., 2012. SURFEX scientific documentation. Geosci. Model Dev. 237.

- Lefebvre, S., Clément, J.C., Pinay, G., Thenail, C., Jurand, P., Marmonier, P., 2007. 15N-nitrate signature in low-order streams: Effects of land cover and agricultural practices. Ecol. Appl. 17. https://doi.org/10.1890/06-1496.1
- Legchenko, A., Baltassat, J.M., Behachev, A., Martin, C., Robain, H., Vouillamoz, J.M., 2004. Magnetic resonance sounding applied to aquifer characterization. Ground Water 42, 363– 373. https://doi.org/10.1111/j.1745-6584.2004.tb02684.x
- Leray, S., de Dreuzy, J.R., Aquilina, L., Vergnaud-Ayraud, V., Labasque, T., Bour, O., Le Borgne, T., 2014. Temporal evolution of age data under transient pumping conditions. J. Hydrol. 511, 555–566. https://doi.org/10.1016/j.jhydrol.2014.01.064
- Liao, L., Green, C.T., Bekins, B.A., Böhlke, J.K., 2012. Factors controlling nitrate fluxes in groundwater in agricultural areas. Water Resour. Res. 48. https://doi.org/10.1029/2011WR011008

Małoszewski, P., Zuber, A., 1982. Determining the turnover time of groundwater systems with

the aid of environmental tracers. 1. Models and their applicability. J. Hydrol. 57, 207–231. https://doi.org/10.1016/0022-1694(82)90147-0

- Marçais, J., de Dreuzy, J.R., Erhel, J., 2017. Dynamic coupling of subsurface and seepage flows solved within a regularized partition formulation. Adv. Water Resour. 109, 94–105. https://doi.org/10.1016/j.advwatres.2017.09.008
- Marçais, J., de Dreuzy, J.R., Ginn, T.R., Rousseau-Gueutin, P., Leray, S., 2015. Inferring transit time distributions from atmospheric tracer data: Assessment of the predictive capacities of Lumped Parameter Models on a 3D crystalline aquifer model. J. Hydrol. 525, 619–631. https://doi.org/10.1016/j.jhydrol.2015.03.055
- Marçais, J., Gauvain, A., Labasque, T., Abbott, B.W., Finay, G., Aquilina, L., Chabaux, F., Viville, D., De Dreuzy, J.-R., 2018. Dating groundwater with dissolved silica and CFC concentrations in crystalline aquifers. Sci. Total Environ. 636, 260–272.
- Maréchal, J.C., Dewandel, B., Subrah, anyam, K., 2004. Use of hydraulic tests at different scales to characterize fracture network properties in the weathered-fractured layer of a hard rock aquifer. Water Resou. Res. 40, 1–17. https://doi.org/10.1029/2004WR003137
- Martin, C., Aquilina, L., Gescuel-Odoux, C., Molénat, J., Faucheux, M., Ruiz, L., 2004. Seasonal and interannual valiations of nitrate and chloride in stream waters related to spatial and temporal patterns of groundwater concentrations in agricultural catchments. Hydrol. Process. 18, 1237–1254. https://doi.org/10.1002/hyp.1395
- Martin, C., Molénat, J., Gascuel-Odoux, C., Vouillamoz, J.M., Robain, H., Ruiz, L., Faucheux, M., Aquilina, L., 2006. Modelling the effect of physical and chemical characteristics of shallow aquifers on water and nitrate transport in small agricultural catchments. J. Hydrol. 326, 25–42. https://doi.org/10.1016/j.jhydrol.2005.10.040

- Masson, V., Le Moigne, P., Martin, E., Faroux, S., Alias, A., Alkama, R., Belamari, S., Barbu, A., Boone, A., Bouyssel, F., Brousseau, P., Brun, E., Calvet, J.C., Carrer, D., Decharme, B., Delire, C., Donier, S., Essaouini, K., Gibelin, A.L., Giordani, H., Habets, F., Jidane, M., Kerdraon, G., Kourzeneva, E., Lafaysse, M., Lafont, S., Lebeaupin Brossier, C., Lemonsu, A., Mahfouf, J.F., Marguinaud, P., Mokhtari, M., Morin, S., Pigeon, G., Salgado, R., Seity, Y., Taillefer, F., Tanguy, G., Tulet, P., Vincendon, B., Vionnet, V., Voldoire, A., 2013. The SURFEXv7.2 land and ocean surface platform for coupled or offline simulation of earth surface variables and fluxes. Geosci. Model Dev. 6, 929–962. https://doi.org/10.5194/gmd-6-929-2013
- Matonse, A.H., Kroll, C., 2009. Simulating low streat. (lows with hillslope storage models. Water Resour. Res. 45, 1–13. https://doi.org/10.11/29/2007WR006529
- McDonald, M.G., Harbaugh, A.W., 19 4. A modular three dimensional finite difference groundwater flow model: U.S. Geological Survey Open File Report 83 875, 528 p.
- Meals, D.W., Dressing, S.A., Davenpurt, T.E., 2010. Lag Time in Water Quality Response to Best Management Practices: A Review. J. Environ. Qual. 39, 85–96. https://doi.org/10.2134/ie.j2009.0108
- MEDDE, GIS Sol, 2014. Enveloppes des milieux potentiellement humides de la France métropolitaine. Notice d'accompagnement. Programme de modélisation des milieux potentiellement humides de France, Ministère de l'Ecologie, du Développement Durable et de l'Energie, Groupement d'I.
- Ménesguen, A., Salommon, J., 1988. Eutrophication modelling as a tool for fighting against Ulva coastal mass blooms. Pap. Present. Comput. Model. Ocean Eng. Venice.

Merot, P., Corgne, S., Delahaye, D., Desnos, P., Dubreuil, V., Gascuel, C., Giteau, J., 2014.

Assessment, impact and perception of climate change in the western part of France: The CLIMASTER project 23, 96–107. https://doi.org/10.1684/agr.2014.0694

- Merot, P., Squividant, H., Aurousseau, P., Hefting, M., Burt, T., Maitre, V., Kruk, M., Butturini, A., Thenail, C., Viaud, V., 2003. Testing a climato-topographic index for predicting wetlands distribution along an European climate gradient. Ecol. Modell. 163, 51–71. https://doi.org/10.1016/S0304-3800(02)00387-3
- Molénat, J., Davy, P., Gascuel-Odoux, C., Durand, P., 1999. Study of three subsurface hydrologic systems based on spectral and cross-spectral cruck sis of time series. J. Hydrol. 222, 152–164. https://doi.org/10.1016/S0022-1694(99, 00107-9
- Molénat, J., Durand, P., Gascuel- Odoux, C., Davy, P. C. uau, G., 2002. Mechanisms of nitrate transfer from soil to stream in agricultural verte shed of French Brittany. Water. Air. Soil Pollut. 133, 161–183.
- Molénat, J., Gascuel-Odoux, C., Aquiline L., Ruiz, L., 2013. Use of gaseous tracers (CFCs and SF6) and transit-time distribution pectrum to validate a shallow groundwater transport model. J. Hydrol. 480, 1–9. https://doi.org/10.1016/j.jhydrol.2012.11.043
- Molenat, J., Gascuel-Odove, C., Ruiz, L., Gruau, G., 2008. Role of water table dynamics on stream nitrate expo.* and concentration in agricultural headwater catchment (France). J. Hydrol. 348, 363–378. https://doi.org/https://doi.org/10.1016/j.jhydrol.2007.10.005
- Montreuil, O., Merot, P., Marmonier, P., 2010. Estimation of nitrate removal by riparian wetlands and streams in agricultural catchments: Effect of discharge and stream order. Freshw. Biol. 55. https://doi.org/10.1111/j.1365-2427.2010.02439.x
- Mougin, B., Allier, D., Blanchin, R., Carn, A., Courtois, N., Gateau, C., Putot, E., 2008. SILURES Bretagne (Système d'Information pour la Localisation et l'Utilisation des

Ressources en Eaux Souterraines).

- Mougin, B., Carn, A., Jegou, J.-P., Quéméner, G., 2006. SILURES Bretagne (Système d' Information pour la Localisation et l'Utilisation des Ressources en Eaux Souterraines).
- Ocampo, C.J., Oldham, C.E., Sivapalan, M., 2006a. Nitrate attenuation in agricultural catchments: Shifting balances between transport and reaction. Water Resour. Res. 42, 1–16. https://doi.org/10.1029/2004WR003773
- Ocampo, C.J., Sivapalan, M., Oldham, C.E., 2006b. Field exploration of coupled hydrological and biogeochemical catchment responses and a unifying proceptual model. Adv. Water Resour. 29, 161–180. https://doi.org/10.1016/j.advwaures.2005.02.014
- Ogden, F.L., Watts, B.A., 2000. Saturated area formation on nonconvergent hillslope topography with shallow soils: A numerical investige tor. Water Resour. Res. 36, 1795–1804. https://doi.org/10.1029/2000WR900C 1
- Oldham, C.E., Farrow, D.E., Peiffer, S., 2013. A generalized Damköhler number for classifying material processing in hytrological systems. Hydrol. Earth Syst. Sci. https://doi.org/10.5194/hes. 17-i133-2013
- Pinault, J.-L., Pauwels, H., 2001. Inverse modeling of the hydrological and the hydrochemical behavior of hydrocystems: Application to nitrate transport and denitrification. Water Resour. 37, 2179–2190.
- Pinay, G., Peiffer, S., De Dreuzy, J.R., Krause, S., Hannah, D.M., Fleckenstein, J.H., Sebilo, M., Bishop, K., Hubert-Moy, L., 2015. Upscaling Nitrogen Removal Capacity from Local Hotspots to Low Stream Orders' Drainage Basins. Ecosystems 18, 1101–1120. https://doi.org/10.1007/s10021-015-9878-5

Poisvert, C., Curie, F., Moatar, F., 2017. Annual agricultural N surplus in France over a 70-year

period. Nutr. Cycl. Agroecosystems 107, 63-78. https://doi.org/10.1007/s10705-016-9814-x

- Quintana-Seguí, P., Le Moigne, P., Durand, Y., Martin, E., Habets, F., Baillon, M., Canellas, C.,
 Franchisteguy, L., Morel, S., 2008. Analysis of near-surface atmospheric variables:
 Validation of the SAFRAN analysis over France. J. Appl. Meteorol. Climatol. 47, 92–107.
 https://doi.org/10.1175/2007JAMC1636.1
- Roques, C., Aquilina, L., Boisson, A., Vergnaud-Ayraud, V., Labasque, T., Longuevergne, L., Laurencelle, M., Dufresne, A., de Dreuzy, J.R., Pauwels, H., Pour, O., 2018a. Autotrophic denitrification supported by biotite dissolution in crystalline equifers: (2) transient mixing and denitrification dynamic during long-term pumpine Sci. Total Environ. 619–620, 491– 503. https://doi.org/10.1016/j.scitotenv.2017.11.104
- Roques, C., Aquilina, L., Boisson, A., Vergnard 'Avraud, V., Labasque, T., Longuevergne, L., Laurencelle, M., Dufresne, A., de Di Yuzy, J.R., Pauwels, H., Bour, O., 2018b. Autotrophic denitrification supported by biotite dissolution in crystalline aquifers: (2) transient mixing and denitrification dynamic during 'ong-term pumping. Sci. Total Environ. 619–620, 491– 503. https://doi.org/10.101c/i.scitotenv.2017.11.104
- Roques, C., Aquilina, L., Pour, O., Maréchal, J.C., Dewandel, B., Pauwels, H., Labasque, T., Vergnaud-Ayraud, V., Hochreutener, R., 2014. Groundwater sources and geochemical processes in a crystalline fault aquifer. J. Hydrol. 519, 3110–3128. https://doi.org/10.1016/j.jhydrol.2014.10.052
- Ruiz, L., Abiven, S., Martin, C., Durand, P., Beaujouan, V., Molénat, J., 2002. Effect on nitrate concentration in stream water of agricultural practices in small catchments in Brittany: II. Temporal variations and mixing processes. Hydrol. Earth Syst. Sci. 6, 507–513. https://doi.org/10.5194/hess-6-507-2002

- Singhal, B.B.S., Gupta, R.P., 2010. Applied hydrogeology of fractured rocks: Second edition, Springer Science & Business Media. https://doi.org/10.1007/978-90-481-8799-7
- Steffen, W., Richardson, K., Rockström, J., Cornell, S.E., Fetzer, I., Bennett, E.M., Biggs, R., Carpenter, S.R., De Vries, W., De Wit, C.A., Folke, C., Gerten, D., Heinke, J., Mace, G.M., Persson, L.M., Ramanathan, V., Reyers, B., Sörlin, S., 2015. Planetary boundaries: Guiding human development on a changing planet. Science (80-.). 347. https://doi.org/10.1126/science.1259855
- Takuya, K., Yoshishige, H., Nobuharu, K., Tadakatsu, Y., Yacuo, C., 1993. Dispersion effect on the apparent nitrogen isotope fractionation factor as ociated with denitrification in soil; Evaluation by a mathematical model. Soil Biol Piochem. https://doi.org/10.1016/0038-0717(93)90134-W
- Tarits, C., Aquilina, L., Ayraud, V., Pauw 's, H., Davy, P., Touchard, F., Bour, O., 2006. Oxido-reduction sequence related to flux variations of groundwater from a fractured basement aquifer (Ploemeur are?, Urance). Appl. Geochemistry 21, 29–47. https://doi.org/10.1016/j.ap.eocnem.2005.09.004
- Tesoriero, A.J., Spruill, T.P., Mew, H.E., Farrell, K.M., Harden, S.L., 2005. Nitrogen transport and transformations in a coastal plain watershed: Influence of geomorphology on flow paths and residence times. Water Resour. Res. 41, 1–15. https://doi.org/10.1029/2003WR002953
- Townley, L.R., 1995. The response of aquifers to periodic forcing. Adv. Water Resour. 18, 125–146. https://doi.org/10.1016/0309-1708(95)00008-7
- Troch, P. a, Paniconi, C., Emiel van Loon, E., 2003. Hillslope-storage Boussinesq model for subsurface flow and variable source areas along complex hillslopes: 1. Formulation and characteristic response. Water Resour. Res. 39, 1316.

https://doi.org/10.1029/2002wr001728

- Troch, P.A., Carrillo, G., Sivapalan, M., Wagener, T., Sawicz, K., 2013. Climate-vegetation-soil interactions and long-term hydrologic partitioning: Signatures of catchment co-evolution. Hydrol. Earth Syst. Sci. 17, 2209–2217. https://doi.org/10.5194/hess-17-2209-2013
- Van Der Velde, Y., De Rooij, G.H., Rozemeijer, J.C., Van Geer, F.C., Broers, H.P., 2010a.
 Nitrate response of a lowland catchment: On the relation between stream concentration and travel time distribution dynamics. Water Resour. Res. 46, 1–17. https://doi.org/10.1029/2010WR009105
- Van Der Velde, Y., De Rooij, G.H., Rozemeijer, J.C., Van Geer, F.C., Broers, H.P., 2010b. Nitrate response of a lowland catchment: On the rendion between stream concentration and travel time distribution dynamics. Water Resour. Res. 46, 1–17. https://doi.org/10.1029/2010WR0091.15
- Van Meter, K.J., Basu, N.B., 2015. Catchment legacies and time lags: A parsimonious watershed model to predict the effects of logacy storage on nitrogen export. PLoS One 10, 1–22. https://doi.org/10.1371/jour.val.pone.0125971
- Van Meter, K.J., Basu, N.B., Yan Cappellen, P., 2017. Two centuries of nitrogen dynamics: Legacy sources and sinks in the Mississippi and Susquehanna River Basins. Global Biogeochem. Cycles 31, 2–23. https://doi.org/10.1002/2016GB005498
- Van Meter, K.J., Basu, N.B., Veenstra, J.J., Burras, C.L., 2016. The nitrogen legacy: Emerging evidence of nitrogen accumulation in anthropogenic landscapes. Environ. Res. Lett. 11. https://doi.org/10.1088/1748-9326/11/3/035014
- Vautier, C., Abhervé, R., Labasque, T., Laverman, A.M., Guillou, A., Chatton, E., Dupont, P., Aquilina, L., de Dreuzy, J.R., 2020. Mapping gas exchanges in headwater streams with

membrane inlet mass spectrometry. J. Hydrol. 581, 124398. https://doi.org/10.1016/j.jhydrol.2019.124398

- Vogel, J.C., 1967. Investigation of groundwater flow with radiocarbon, in: Isotopes in Hydrology.
- Vrugt, J.A., Sadegh, M., 2013. Toward diagnostic model calibration and evaluation: Approximate Bayesian computation. Water Resour. Res. 49, 4335–4345. https://doi.org/10.1002/wrcr.20354
- Wade, A.J., Durand, P., Beaujouan, V., Wessel, W.W., Raat Y.J., Whitehead, P.G., Butterfield,
 D., Rankinen, K., Lepisto, A., 2002. A nitrogen model for European catchments: INCA, new model structure and equations. Hydrol: Earth Syst. Sci. 6, 559–582. https://doi.org/10.5194/hess-6-559-2002
- Withers, P.J.A., Neal, C., Jarvie, H.P., Oor dy, D.G., 2014. Agriculture and eutrophication: Where do we go from here? Sustain. 6, 5853–5875. https://doi.org/10.3390/su6095853
- Wriedt, G., Rode, M., 2006. Modelling nitrate transport and turnover in a lowland catchment system. J. Hydrol. 328, 157–176. https://doi.org/10.1016/j.jhydrol.2005.12.017
- Wright, E.P., Burgess, W.C. 1992. The hydrogeology of crystalline basement aquifers in Africa, Geological Society, London, Special Publications.
- Wyns, R., Baltassat, J.M., Lachassagne, P., Legchenko, A., Vairon, J., Mathieu, F., 2004. Application of proton magnetic resonance soundings to groundwater reserve mapping in weathered basement rocks (Brittany, France). Bull. la Soc. Geol. Fr. 175, 21–34. https://doi.org/10.2113/175.1.21
- Yoshida, T., Troch, P.A., 2016. Coevolution of volcanic catchments in Japan. Hydrol. Earth Syst. Sci. 20, 1133–1150. https://doi.org/10.5194/hess-20-1133-2016

- Zarnetske, J.P., Haggerty, R., Wondzell, S.M., Baker, M.A., 2011. Dynamics of nitrate production and removal as a function of residence time in the hyporheic zone. J. Geophys. Res. Biogeosciences 116, 1–12. https://doi.org/10.1029/2010JG001356
- Zarnetske, J.P., Haggerty, R., Wondzell, S.M., Bokil, V.A., González-Pinzón, R., 2012. Coupled transport and reaction kinetics control the nitrate source-sink function of hyporheic zones. Water Resour. Res. https://doi.org/10.1029/2012WR011894
- Zheng, C., Wang, P., 1999. MT3DMS: A modular three dimensional multispeces transport model for simulation of advection, dispersion, and chemical reactions of contaminants in groundwater systems. Technical report, Waterways Experiment Station, US Army Corps of Engineers. A Modul. three-dimensional multi-species ... 239.

69

Luca Guillaumot : Data Collection, Conceptualization, Methodology, Software, Data Curation,

Credit Author Statement

Writing - Original Draft, Writing - Review & Editing, Visualization Jean Marçais : Methodology, Writing - Review & Editing, Visualization Camille Vautier : Data Collection, Writing - Original Draft Aurélie Guillou : Data Curation, Data Collection Virginie Vergnaud : Data Curation Camille Bouchez : Writing - Review & Editing Rémi Dupas : Writing - Review & Editing Patrick Durand : Methodology, Software, Writin ξ - Peview & Editing Jean-Raynald de Dreuzy : Conceptualization Mcthodology, Writing - Review & Editing Luc Aquilina : Conceptualization, Methodology, Writing - Review & Editing, Project administration, Funding acquisition
Declaration of interests

 \boxtimes The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

□The authors declare the following financial interests/personal relationships which may be considered as potential competing interests:

Abstract

The long-term fate of agricultural nitrate depends on rapid subsurface transfer, denitrification and storage in aquifers. Quantifying these processes remains an issue due to time varying subsurface contribution, unknown aquifer storage and heterogeneous denitrification potential. Here, we develop a parsimonious modelling approach that uses long-term discharge and river nitrate concentration time-series combined with groundwater age data determined from chlorofluorocarbons in springs and boreholes. To leverage their informational content, we use a Boussinesq-type equivalent hillslope model to capture the dynamics of aquifer flows and evolving surface and subsurface contribution to river. In trate transport was modelled with a depth-resolved high-order finite-difference me not and denitrification by a first-order law. We applied the method to three heavily nitive loaded catchments of a crystalline temperate region of France (Brittany). We found that mean water transit time ranged 10-32 years and Damköhler ratio (transit time / denitrification time) ranged 0.12-0.55, leading to limited denitrification in the aquifer (10-20%). The long-term trajectory of nitrate concentration in rivers appears determined by flows stratification in the aquifer. The results suggest that autotrophic denitrification is controlled by the accessibility of reduced minerals which occurs at the base of the aquifer where flows decrease. One interpretation is that denitrification might be an interfacial process in zones that are weathered enough to transmit flows and not too weathered to have remaining accessible reduced minerals. Consequently, denitrification would not be controlled by the total aquifer volume and related mean transit time but by the proximity of the active weathered interface with the water table. This should be confirmed by complementary studies to which the developed methodology might be further deployed.

Journal Pre-proof



Highlights

- A parsimonious model constrained by discharge, nitrate and CFC concentrations.
- Aquifer volume and young water contribution govern nitrate trends in rivers.
- Groundwater transit time stratification explains nitrate trends in rivers.
- Weak denitrification (~10-20%) occurs only in the deepest part of the aquifer.

Solution of the second