



First results from the Sweeping Langmuir Probe (SLP) instrument on board PICASSO

S. Ranvier¹, J. De Keyser¹, J.P. Lebreton²

¹ Royal Belgian Institute for Space Aeronomy (BIRA-IASB), Belgium ² Laboratoire de Physique et Chimie de l'Environnement et de l'Espace (LPC2E), France

sylvain.ranvier@aeronomie.be

EGU presentation EGU21-9915 GI3.2 29.04.2021

PICASSO mission and platform

Launched on 03.09.2020 with Vega VV16

<u>Orbit:</u>

Apogee: 539 km Perigee: 535 km Inclination: 97.52 degrees

Expected orbital lifetime: 2 years

<u>Platform:</u> 3U CubeSat 1U for payload





PICASSO mission and platform

PIKASS

- Four deployable solar panels
- Dimensions: 340.5 x 100 x 100 mm
- Mass: 3.9 kg
- UHF/VHF
- S-band

PICASSO mission and platform

Payload

SLP (Sweeping Langmuir Probe): Four channel Langmuir probe instrument Fully developed at BIRA-IASB

Measurements:

Plasma density, electron temperature and spacecraft potential

<u>VISION</u> (Visible Spectral Imager for Occultation and Nightglow): Visible and near-infrared hyper-spectral imager HW: VTT, Finland; SW: BIRA-IASB

Objectives:

- Retrieve polar and mid-latitude stratospheric ozone vertical profile
- Upper atmosphere temperature profile based on the Sun refractive flattening

SLP: scientific objectives

Expected plasma parameters

	Minimum	Maximum
Plasma density (#/m³)	10 ⁸	10 ¹³
Electron temperature (K)	600	10 000
Debye length (m)	5.4e-4	0.69

Ionosphere-plasmasphere coupling

Study field-aligned density distribution and temperature effects



SLP: scientific objectives cont.

- Aurora structures
- Polar cap arcs
- Ionospheric dynamics

Coordinated observations with EISCAT's heating radar







SLP: Measurement principle

Based on conventional Langmuir probe theory



3 regions



- Ion density derived from ion saturation region
- Electron T[°] and S/C potential retrieved from electron retardation region
- Electron density derived from electron saturation region

SLP: Measurement modes

- 1. Nominal mode
- Limited downlink bandwidth => reduced # of steps
- 3 regions measured with different step sizes
- Ion and e- saturation regions: large voltage step size (> 1 V)
- Electron retardation region: adapted to e- T°
 e.g.with 30 steps
 Step size from ~ 10 mV to 150 mV for e- T° of 600 K and 10.000 K
- With 43 samples / sweep => up to 45 sweeps / s

=> ~ 170 m spatial resolution for Ne, Te, Ni and S/C potential



From PhD Thesis of A. Barjatya, 2007

SLP: Measurement modes

- 2. Fixed-bias mode (e⁻ density only)
- Based on m-NLP principle
- Constant bias in e⁻ sat. region
- Retrieve only e⁻ density
- Use at least 2 probes simultaneously
- Sampling freq.: 5 KHz
- Spatial resolution ~ 1,5 m
- Can be used to study turbulence
- Large data volume !!



From PhD Thesis of A. Barjatya, 2007



SLP: Measurement modes

3. Monitoring mode

- Assess the amount of contamination of probe surface
- Can be used to study long term ATOX effects (on both the probe and spacecraft surface materials)
- Sweep in both directions
- Different sweep durations





S/C charging

Limited conducting area of the S/C with respect to the area of the probe

=> Spacecraft charging (e- saturation region)

=> Drift of the instrument's electrical ground during the measurement

Proposed solution

Measure the floating potential of one probe while measuring the I-V curve with another probe

Advantages:

- Robust: no filament
- No risk of electron collection from e-gun
- Gives insight about S/C charging

HW: Probes

- 4 identical probes
- 40 mm Ti tubes of 2 mm diameter
- Attached to the extremity of the solar panels via 40 mm boom
- Gold plated
- Mass of assembly: 6 g



HW: Electronics box



Electronics box

- 104 x 98 x 25 mm
- Power (average): 2.2 W



Mass:

SLP Electronics	87 g
Shielding cover	41 g
4 Booms/probes Incl. interface and harness	24 g
TOTAL SLP MASS	152 g



Current status

- PICASSO platform still in commissioning phase
 - \Rightarrow Very limited usage of payload, attitude knowledge only in sunlight \Rightarrow no science data yet
- All SLP health indicators are nominal (internal voltages, temperature at different locations on the electronic boards, communication with payload computer, booting sequence, internal current source, etc.)
- One probe, which was functioning nominally during the first 3 months, seems to be disconnected (probably a soldering crack at the base of the probe)
 => Not critical: the four channels and probes are exactly identical (all can be used either as traditional LP or to measure the floating potential): full redundancy

First results: linear sweep

Example of linear sweep with equidistant steps:

- -5 V to + 5 V
- 200 samples
- I-V sweep : probe #1
- Floating probe: probe #3
- \Rightarrow Clean data



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



I-V curve. Linear scale



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).

Bias (V) I-V curve. Semi-log scale

-2

I-V curve



Potential measured with floating probe

First results: adaptive sweep

Example of adaptive sweep:

- -5 V to + 5 V
- 60 samples:
- 5 in ion saturation region
- ➢ 50 in e- retardation region
- 5 in e- saturation region
- I-V sweep : probe #1
- Floating probe: probe #3
- ⇒ e- retardation region well resolved



I-V curve. Linear scale

I-V curve. Semi-log scale.

6



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Potential measured with floating probe.

First results: fixed-bias mode

Example of fixed-bias measurement:

- Probe #1: floating probe
- Probe #2: 4 V
- Probe #3: 3 V
- 1k sample / s
- In sunlight
- ⇒ Noise structures from the platform visible both on current and potential



Current from probe #2



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Potential measured with floating probe.

First results: fixed-bias mode

Longer fixed-bias measurement in sunlight

- Probe #1: 6 V
- Probe #2: 4 V
- Probe #3: floating probe
- 1k sample / s
- ⇒ Noise structures from the platform visible both on current and potential



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Attitude of PICASSO wrt velocity vector (black arrow) and Sun direction (yellow).



Current from probe #1

Potential measured with floating probe.

time [ms

 $\times 10^4$

First results: fixed-bias mode

Longer fixed-bias measurement in eclipse

- Probe #1: 6 V
- Probe #2: 4 V
- Probe #3: floating probe
- 1k sample / s
- \Rightarrow No noise structures in eclipse

⇒ Noise attributed to Battery Charge Regulator (BCR)

• Timing and duration of noise structures in sunlight compatible with BCR-originated noise



Current from probe #1



Potential measured with floating probe.

Conclusions

- PICASSO platform still in commissioning phase ⇒ Limited number of measurements
- SLP health is nominal except that one probe seems to be disconnected ⇒ Not critical since all four channels are identical (full redundancy)
- All SLP modes have been successfully tested
- Both linear and adaptive sweeps produce clean I-V curves
- Noise structures are visible when measuring in sunlight
 - ⇒ Preliminary tests indicate it is related to the Battery Charge Regulator (BCR) of the platform
 - \Rightarrow Still possible to perform I-V sweeps in sunlight, even if some curves are perturbed by the noise
 - \Rightarrow More of a problem for fixed-bias mode
- Assessment of probe surface contamination on going
- Next steps:
 - Validation of SLP data with EISCAT data (coordinated campaign)
 - When platform commissioning completed: start science mode

Acknowledgement

This project has been supported by

- BELSPO (Belgian Scientific Policy Office)
- STCE (Solar-Terrestrial Center of Excellence)
- ESA contract 4000112430/14/NL/MH

Thank you !

For more information: please contact sylvain.ranvier@aeronomie.be